

SENTEN

Symposium of Emerging Nuclear
Technology and Engineering Novelty



Certificate

THIS CERTIFICATE IS PROUDLY PRESENTED TO

Ahmad Rezhani Fitra

as : participant / presenter / guest / comittee*

SENTEN 2018

Symposium of Emerging Nuclear Technology and Engineering Novelty
Palembang, 4-5th July 2018

"Discovering
Science and Engineering Novelty
for improving human life prosperity"

Head of Center for Nuclear Reactor
Technolofy and Safety

Dr. Geni R. Sunayo, M.Sc

Dean of Engineering Faculty
Sriwijaya University

Prof. Ir. Subriyer Nasir, M.S., Ph.D.

LEMBAR
HASIL PENILAIAN SEJAWAT SEBIDANG (PEER REVIEW)
KARYA ILMIAH: PROSIDING MAKALAH SEMINAR INTERNASIONAL TERINDEKS

Judul Karya Ilmiah : Efficiency Analysis of Suban Irrigation System, West Tanjung Jabung, Jambi Province

Jumlah Penulis : 3 (Tiga) Orang : Ahmad Rezhani Fitra, Dinar DA Putranto, Sarino

Identitas Prosiding : a. Nama Prosiding : SENTEN 2018- Symposium of Emerging Nuclear Technology and Engineering Novelty
 b. ISBN/ISSN :
 c. Nomor/Volume/Hal. : [Volume 1198](#) (2019) 082026
 d. Penerbit : Published under licence by IOP Publishing Ltd
[Journal of Physics: Conference Series, Volume 1198, Architecture and Civil Engineering](#)
 e. Jumlah Halaman : 5 (lima) Halaman

Kategori Publikasi : Prosiding Forum Ilmiah Internasional
 Prosiding Forum Ilmiah Nasional
 Makalah Disajikan dan dimuat dalam prosiding Seminar/Symposium/Lokakarya Internasional
 Makalah Disajikan dan dimuat dalam prosiding Seminar/Symposium/Lokakarya Nasional
 Makalah Tidak disajikan tetapi dimuat dalam prosiding Seminar/Symposium/Lokakarya Internasional
 Makalah Tidak disajikan tetapi dimuat dalam prosiding Seminar/Symposium/Lokakarya Nasional
 Makalah Disajikan dalam seminar/Symposium Internasional Tetapi tidak dimuat dalam prosiding
 Makalah Tidak disajikan tetapi dimuat dalam prosiding Seminar Internasional

I. Hasil Penilaian Validasi :

No.	Aspek	URAIAN/KOMENTAR PENILAIAN
1	Indikasi Plagiasi	Similarity Indeks kurang dari 10 %
2	Linieritas	Kesamaan dalam bidang Survei dan Pemetaan dalam perencanaan Irigasi

II. Hasil Penilaian Peer Review

Komponen yang dinilai	Nilai Maksimal Makalah Ilmiah/Prosiding (Isikan di Kolom yang sesuai)						Nilai Akhir yang diperoleh
	Prosiding Forum Ilmiah Internasional (Max.15)	Prosiding Forum Ilmiah Nasional (Max.10)	Makalah Tidak diseminarkan Tetapi dimuat dalam Prosiding Internasional (Maks.10)	Makalah Tidak diseminarkan Tetapi dimuat dalam Prosiding Nasional (Maks.5)	Makalah Diseminarkan tetapi Tidak dimuat dalam Prosiding Internasional (Maks.5)	Makalah Tidak diseminarkan Tetapi dimuat dalam Prosiding Nasional (Maks.3)	
Kelengkapan dan Kesesuaian unsur isi paper (20 %)	1,5						1
Ruang Lingkup dan kedalaman pembahasan (10 %)	4,5						3
Kecukupan dan Kemutakhiran data/Informasi dan metodologi (30 %)	4,5						3
Kelengkapan unsur dan Kualitas penerbit/prosiding (20 %)	4,5						4
Total = (100 %)	15						11
Kontribusi Pengusul (Penulis Pertama/Anggota Utama)	Pengusul mempunyai kontribusi yang baik dalam menyusun metode penilaian survey lapangan dalam melihat permasalahan ketidaksesuaian antara perencanaan dan pelaksanaan di lapangan						
KOMENTAR/ULASAN PEER REVIEW							
Kelengkapan dan Kesesuaian Unsur			Unsur kelengkapan sudah sesuai				
Ruang Lingkup dan Kedalaman Pembahasan			Bahasan dilakukan dengan baik dan sesuai				
Kecukupan dan & Kemutakhiran Data & Metodologi			Data yang digunakan cukup baik, hasil survey lapangan sehingga analisis sesuai				
Kelengkapan Unsur dan Kualitas Penerbit			Penerbit dan kualitas penyelenggara seminar terindeks dalam database bereputasi				

Surabaya, 29 Mei 2018
 Penilai

Nama : Prof. Dr. Ir. Bangun Muljo Sukojo, DEA, DESS
 NIP : 195305271983031001
 Unit Kerja : Fakultas Teknik Sipil, Lingkungan dan Kebumihan Institut Teknologi Sepuluh Nopember Surabaya
 Bidang Ilmu : Geomatika
 Jabatan/Pangkat : Guru Besar/Pembina IV e

LEMBAR
HASIL PENILAIAN SEJAWAT SEBIDANG (PEER REVIEW)
KARYA ILMIAH: PROSIDING MAKALAH SEMINAR INTERNASIONAL TERINDEKS

Judul Karya Ilmiah : Efficiency Analysis of Suban Irrigation System, West Tanjung Jabung, Jambi Province

Jumlah Penulis : 3 (Tiga) Orang : Ahmad Rezhani Fitra, Dinar DA Putranto, Sarino

Identitas Prosiding :

- a. Nama Prosiding : SENTEN 2018- Symposium of Emerging Nuclear Technology and Engineering Novelty
- b. ISBN/ISSN :
- c. Nomor/Volume/Hal. : [Volume 1198](#) (2019) 082026
- d. Penerbit : Published under licence by IOP Publishing Ltd
[Journal of Physics: Conference Series, Volume 1198, Architecture and Civil Engineering](#)
- e. Jumlah Halaman : 5 (lima) Halaman

Kategori Publikasi :

- Prosiding Forum Ilmiah Internasional
- Prosiding Forum Ilmiah Nasional
- Makalah Disajikan dan dimuat dalam prosiding Seminar/Symposium/Lokakarya Internasional
- Makalah Disajikan dan dimuat dalam prosiding Seminar/Symposium/Lokakarya Nasional
- Makalah Tidak disajikan tetapi dimuat dalam prosiding Seminar/Symposium/Lokakarya Internasional
- Makalah Tidak disajikan tetapi dimuat dalam prosiding Seminar/Symposium/Lokakarya Nasional
- Makalah Disajikan dalam seminar/Symposium Internasional Tetapi tidak dimuat dalam prosiding
- Makalah Tidak disajikan tetapi dimuat dalam prosiding Seminar Internasional

I. Hasil Penilaian Validasi :

No.	Aspek	URAIAN/KOMENTAR PENILAIAN
1	Indikasi Plagiasi	Similarity Indeks kurang dari 10 %
2	Linieritas	Metode pengukuran data dan survey Lapangan sesuai bidang pengukuran dan pemetaan

II. Hasil Penilaian Peer Review

Komponen yang dinilai	Nilai Maksimal Makalah Ilmiah/Prosiding (Isikan di Kolom yang sesuai)						Nilai Akhir yang diperoleh
	Prosiding Forum Ilmiah Internasional (Max.15)	Prosiding Forum Ilmiah Nasional (Max.10)	Makalah Tidak diseminarkan Tetapi dimuat dalam Prosiding Internasional (Maks.10)	Makalah Tidak diseminarkan Tetapi dimuat dalam Prosiding Nasional (Maks.5)	Makalah Diseminarkan tetapi Tidak dimuat dalam Prosiding Internasional (Maks.5)	Makalah Tidak diseminarkan Tetapi dimuat dalam Prosiding Nasional (Maks.3)	
Kelengkapan dan Kesesuaian unsur isi paper (20 %)	1,5						1
Ruang Lingkup dan kedalaman pembahasan (10 %)	4,5						4
Kecukupan dan Kemutahiran data/Informasi dan metodologi (30 %)	4,5						3,5
Kelengkapan unsur dan Kualitas penerbit/prosiding (20 %)	4,5						4
Total = (100 %)	15						12,5
Kontribusi Pengusul (Penulis Pertama/Anggota Utama)	Sumbangan metode pengukuran yang diberikan pengusul sangat membantu dalam pelaksanaan pengumpulan data di lapangan						
KOMENTAR/ULASAN PEER REVIEW							
Kelengkapan dan Kesesuaian Unsur			Unsur-unsur kelengkapan dalam penulisan paper sesuai kaidah yang disyaratkan				
Ruang Lingkup dan Kedalaman Pembahasan			Ruang lingkup materi penelitian sesuai dengan bahasan yang disajikan				
Kecukupan dan & Kemutahiran Data & Metodologi			Metodologi perolehan data dan analisis serta ruang lingkupnya sesuai dan cukup baik				
Kelengkapan Unsur dan Kualitas Penerbit			Penerbit dan kualitas penyelenggara seminar terindeks dalam database bereputasi				

Bogor., 18 Mei 2018

Penilai



Nama : Prof. Dr. Ir. Vincentius Paulus Siregar, DEA

NIP : 195611031985031000

Unit Kerja : Fakultas Perikanan dan Ilmu Kelautan
Institut Pertanian Bogor

Bidang Ilmu : Penginderaan Jauh dan GIS

Jabatan/ Pangkat : Guru Besar/Pembina IV B

Fitra_2019_J._Phys._Conf._Ser _1198_082026

by Dinar Putranto

Submission date: 26-Jun-2019 09:40AM (UTC+0700)

Submission ID: 1147108758

File name: Fitra_2019_J._Phys._Conf._Ser._1198_082026.pdf (412.97K)

Word count: 2255

Character count: 10499

PAPER • OPEN ACCESS

Efficiency Analysis of Suban Irrigation System, West Tanjung Jabung, Jambi Province

1

To cite this article: Achmad Rezhani Fitra *et al* 2019 *J. Phys.: Conf. Ser.* **1198** 082026

View the [article online](#) for updates and enhancements.



IOP | ebooks™

Bringing you innovative digital publishing with leading voices to create your essential collection of books in STEM research.

Start exploring the collection - download the first chapter of every title for free.

Efficiency Analysis of Suban Irrigation System, West Tanjung Jabung, Jambi Province

Achmad Rezhani Fitra, Dinar DA Putranto, Sarino

Department of Civil Engineering of Faculty of Engineering of Sriwijaya University,
Palembang, Indonesia

Corresponding author: dwanugerah@yahoo.co.id

Abstract. Water losses on the irrigation area affect the efficiency level of the drainage on the irrigation system, distribution of water can be told as efficient if the discharge of water which distribute by irrigation drainage optimally match to the need of water on the agricultural field. The purposes of this research are to analyze how much water losses on the primary drainage and secondary drainage and also to analyze the efficiency achieved on the water distribution of the Suban River Irrigation System. Efficiency and Water losses analyzed with measurement of incoming discharge and outcoming discharge on the primary drainage and secondary drainage, then for the measurement of flow velocity by the buoy method. Based on the analysis, total of water losses on the Suban Irrigation system is 6.46% and efficiency value on the primary drainage as 92.32%, efficiency value on the secondary left drainage as 95.40% and efficiency value on the secondary right drainage as 92.90%. From the efficiency of drainage it can be obtained that the total efficiency of drainage as 93.54%, which the Irrigation System of the Suban river classified as good condition.

1. Introduction

Overused of the water, uncontrolled distribution system and many of people that still taking the water for the daily activity were the factors that happen on the Irrigation area in Indonesia. So, it required to saving the water. Save the water can describe as the activity to achieve effective and efficient situation, there are amount water that gave larger advantage than previous condition.

Suban Irrigation area have the water distribution problem, located in West Tanjung Jabung regency. Suban irrigation area known as largest technical Irrigation in Jambi province, which has 5 times of planting per 2 years and productivity as ± 6 ton/ha. Suban Irrigation area is the potential food security supporter on the Jambi province, which functionally actived about 910 Ha from the 1.121 Ha potential on the area. However, Suban Irrigation area have deficiency of water caused by dry season, which indicated the wrong procedure for the exploitation and utilization of the drainage.

Based on the problem occurred at the Suban Irrigation area, needed the necessary to reevaluate the efficiency level of Irrigation drainage at the Suban Irrigation area by analyzing the loss water value and drainage efficiency value which achieved from water distribution on Irrigation system of Suban Irrigation area.

2. Method

2.1. Research Area

The research area located at Batang Asam district, West Tanjung Jabung reGENCY Jambi province, and the location can be reach by car for ± 3 hours from Jambi. Suban Dam located at Suban village, while 1.800 m left drainage located at Rawa Medang village which serving 480 Ha and 3.565 m secondary right drainage located at Sri Agung reGENCY serving 430 Ha. Potentially serving area of Suban Irrigation area widely about 1121 Ha and 910 Ha area functionally as rice field and produce ± 6 tonne/Ha with Rice-Rice-Secondary Crop pattern.

2.2. Method of Research

The method of this research is analysis of observation. The analysis was doing by Inflow and Outflow discharge water use conventional equation.

2.2.1. Tools

The tools that used are flow velocity and wet section measurement tools such as mineral water bottle as buoy, rope, measuring strap, depth stick, stopwatch, stationary, paint

2.2.2. Location

Measurement location selected on the primary and secondary drainage row which fullfil the requirements on the flow velocity measurement and wet section measurement. Measurement located on the upstream and the downstream of drainage, then for measuring the flow velocity it used Buoy method. The Measurement held about 3 times, where the buoy position situated on the right side, centre side and left side of the flow.




Figure 1. Point of measurement scheme of Suban Irrigation system

2.3. Calculation Method

2.3.1. Discharge Calculation

Discharge or drainage flow value is flow volume that stream through a cross-section of drainage per time unit (m³/s). Basically, the discharge measurement is metering the wet section area, flow velocity and level of water. The formula used is:

$$Q = \Sigma (A \times V) \tag{1}$$

Where :

- Q = Discharge (m³/s)
- A = Wide area of wet section (m²)
- V = Drainage average Flow velocity (m/sec)

Table 1. Calculation of discharge of the primary drainage and secondary drainage

Location of Measurement	Wide Area of Wet Section (m ²)	Flow Velocity (m/sec)	Water Discharge (m ³ /sec)
Primary drainage			
Row 1 (inflow)	3.04	0.46	1.40
Row 1 (outflow)	2.10	0.58	1.21
Row 2 (inflow)	2.37	0.50	1.17
Row 2 (outflow)	3.00	0.39	1.16
Left secondary drainage			
Row 1 (inflow)	0.59	0.56	0.33
Row 1 (outflow)	0.42	0.74	0.31
Row 2 (inflow)	0.66	0.46	0.31
Row 2 (outflow)	1.18	0.24	0.29
Row 3 (inflow)	0.39	0.72	0.28
Row 3 (outflow)	0.52	0.51	0.27
Row 4 (inflow)	0.36	0.38	0.14
Row 4 (outflow)	0.36	0.37	0.13
Right secondary drainage			
Row 1 (inflow)	1.31	0.61	0.79
Row 1 (outflow)	1.29	0.60	0.78
Row 2 (inflow)	1.20	0.58	0.69
Row 2 (outflow)	1.47	0.46	0.68
Row 3 (inflow)	0.77	0.78	0.60
Row 3 (outflow)	0.51	1.01	0.51
Row 4 (inflow)	0.32	1.33	0.43
Row 4 (outflow)	0.39	0.98	0.38

2.3.2. Water losses

Irrigation Water losses that happens at the water distribution especially caused by seepage on the drainage, evaporation (commonly small) and operational losses occurs when the run-off and spillover of disposal water at the drainage operation time and also over exploitation of water by the farmer.

Water losses in every Inflow – outflow measurement calculated as deviation of the inflow discharge and outflow discharge.

$$h_n = I_n - O_n \tag{2}$$

Where :

- H_n = Water losses on the measured row/section of drainage n (m³/s)
- I_n = Inflow measured n (m³/s)
- O_n = Outflow measured n (m³/s)

2.3.3. Efficiency of Irrigation

Efficiency of irrigation is based on the reality that not all of the water drainage which given or tapped and pull in to the drainage can be flown to the next tapped building or plotland, but there are the parts of missing or not being utilized. Generally the efficiency of irrigation defined as ration between amount of water given minus Water losses where the amount of water given as percent.

$$Ec = (Q_{out} / Q_{in}) \times 100\% \tag{3}$$

Where :

- Ec = Efficiency of distribution
- Q out = Discharge outflow (m³/s)
- Q in = Discharge inflow (m³/s)

2.4. Analysis Method

Analysis method by data processing that used on the research, are:

- a. Discharge inflow and outflow analysis on the primary and secondary drainage
- b. Water losses analysis and efficiency of irrigation system

3. Result

3.1. Discharge inflow and discharge outflow analysis on the primary and secondary drainage

Discharge inflow and discharge outflow analysis based on the measured data of flow velocity with buoy method and wide area of wet section of draiage. Calculation result of discharge flow as seen table 1:

3.2. Water losses analysis and efficiency of irrigation system

Water losses and efficiency at the analysis of every row measurement with distance depends on the drainage distance, both primary and secondary at table 2.

Table 2. Water losses analysis and efficiency

Location of Measurement	Water Discharge (m3/sec)			Efficiency (%)	Drainage Efficiency (%)	Percentage Water Losses (%)
	In	On	hn	Ec		
Primary drainage						
Row 1	1.40	1.21	0.20	86.02	92.32	7.68
Row 2	1.17	1.16	0.02	98.62		
Left secondary drainage						
Row 1	0.33	0.31	0.02	94.27	95.40	4.60
Row 2	0.31	0.29	0.02	93.56		
Row 3	0.28	0.27	0.01	95.61		
Row 4	0.14	0.13	0.00	98.15		
Right Secondary drainage						
Row 1	0.79	0.78	0.01	98.43	92.90	7.10
Row 2	0.69	0.68	0.01	98.59		
Row 3	0.60	0.51	0.09	85.59		
Row 4	0.43	0.38	0.05	89.01		
Primary and Secondary Drainage Efficiency					93.54	
Water Losses in Primary and Secondary Drainage						6.46

4. Conclusion

Based on the result discussion it can be concludes that:

1. Efficiency of water distribution on the system :
 - a. Efficiency of primary drainage averagely as 92.32% for the 1.690 m long drainage. Loss water on the primary drainage is 7.68%.
 - b. Efficiency of left drainage averagely as 95.40% for the 1.800 m long drainage.
 - c. Efficiency of right drainage averagely as 92.90% for the 3.565 m long drainage.
2. Water losseses overally at the Irrigation sytem of Suban irrigation area is 6.46%, the losses water causing by physical factors of drainage, to illegal water taking for daily needs and fish ponds.

References

- [1]. Anonim., 2012. Standar Perencanaan Irigasi, Kriteria Perencanaan 03 Direktorat Jenderal

Sumber Daya Air. Departemen Pekerjaan Umum dan Perumahan Rakyat Jakarta.

- [2]. Suyono Sasrodarsono., Takeda Kensaku., 2003. Hidrologi untuk Pengairan Pradnya Paramita. Jakarta.
- [3]. M. G. Bos., J. Nugteren., 1982. On Irrigation Efficiencies International Institut for Land Reclamation and Improvement Wageningen.
- [4]. Wihelmus Bunganaen., 2011. Analisis Efisiensi dan Kehilangan Air pada Jaringan Utama Daerah Irigasi Air Sagu Jurnal Efisiensi Irigasi.
- [5]. Agus Sumadiyono., 2012. Analisis Efisiensi Pemberian Air di Jaringan Irigasi Karau Kabupaten Barito Timur Provinsi Kalimantan Tengah Jurnal Efisiensi Irigasi.
- [6]. Ahmad Ansori., Anton Ariyanto., Syahroni., 2013. Kajian Efektifitas dan Efisiensi Jaringan Irigasi Terhadap Kebutuhan Air Pada Tanaman Padi (Studi Kasus Irigasi Kaito Samo Kecamatan Rambah Kabupaten Rokan Hulu) Jurnal Efisiensi Irigasi.
- [7]. Maimun Rizalihadi., Amir Fauzi., Reza Tanzil., 2014. Evaluasi Kinerja Irigasi dari Aspek Konsistensi Efisiensi Irigasi pada Daerah Irigasi Pandrah Birieun Aceh Jurnal Efisiensi Irigasi.
- [8]. Akmal., Masimin., Ella meilianda., 2014. Efisiensi Irigasi Pada Petak Tersier di Daerah Irigasi Lawe Bulan Kabupaten Aceh Tenggara Jurnal Efisiensi Irigasi.

ORIGINALITY REPORT

10%	8%	10%	11%
SIMILARITY INDEX	INTERNET SOURCES	PUBLICATIONS	STUDENT PAPERS

PRIMARY SOURCES

1	Submitted to Sriwijaya University Student Paper	8%
2	dspace.vutbr.cz Internet Source	2%

Exclude quotes On
Exclude bibliography On

Exclude matches < 1%