Influence of the Rubber Seed Type and Altitude on Characteristic of Seed, Oil and Biodiesel

by Salni Salni

Submission date: 01-May-2020 07:29AM (UTC+0700) Submission ID: 1312650301 File name: salni_ijred_2017.pdf (690.33K) Word count: 5068 Character count: 25409



IJRED

Contents list available at IJRED website Int. Journal of Renewable Energy Development (IJRED) Journal homepage: http://ejournal.undip.ac.id/index.php/ijred

Tank Reneate Iney Doutpert

Page | 157

Influence of the Rubber Seed Type and Altitude on Characteristic of Seed, Oil and Biodiesel

Salni^a, Poedji Loekitowati Hariani^{b*} and Hanifa Marisa^a

^a Department of Biology, Faculty of Mathematics and Natural Science, Sriwijaya University, Indonesia

^bDepartment of Chemistry, Faculty of Mathematics and Natural Science, Sriwijaya University, Indonesia

ABSTRACT. This research studies the influence of the type of rubber seed that is superior and local, altitude plant in South Sumatra province to the characteristic of seed, oil and biodiesel (methyl ester). Rubber plants planted from local rubber seed by seeds seedlings and superior rubber seed by selected clones. In the study, rubber plants planted at a different altitude, namely in Banyuasin district (18 m above sea level), Prabumulih District (176 m above sea level) and Lahat District (627 m above sea level). The results showed that the weight of the flour, the water content and ash content in the major of fatty acids in the rubber seed oil in all types and altitude, but oil content a large in the superior rubber seeds. The major of fatty acids in the rubber seed oil in all types and altitude are a linoleic 39 d with a different percentage except local rubber seed oil from Lahat district with the large percentage of octadecanoic acid. Free fatty acids in the oil from the superior seeds rubber of 13.897-15.494 % large than local rubber seed oil was found 9.786-10.399 % for all altitude. By esterification process using sulfuric acid catalyst, Free Fatty Acid (F 13 can be reduced to ≤ 2 %. The methyl ester made from the transesterification process of rubber seed oil after esterification using methanol and sodium hydroxide as catalyst. Analysis of methyl esters includes cetane index, flash point, kinematic viscosity, carbon residue, density, moisture content, v30 r and sediment content and distillation compared with SNI 182 and ASTM 6751-02. The result indica 20 that the quality of methyl ester from superior rubber 5 red oil in the Banyuasin and Prabumulih district better than another methyl ester. The types of rubber seed altitude affect the characteristics of the seed, oil and methyl ester but the altitude are not significantly different.

Keywords: rubber seed, type, altitude, oil, biodiesel

Article History: Received March 21st 2017; Received in revised form May 5th 2017; Accepted June 2nd 2017; Available online How to Cite This Article 1 alni, S, Hariani, P.L. and Marisa, H. (2017) Influence the Rubber Seed Type and Altitude on Characteristic of Seed, Oil and Biodiesel. International Journal of Renewable Energy Development, 6(2), 157-163. https://doi.org/10.14710/ijred.6.2.157-163

1. Introduction

Biodiesel (methyl ester) is an alternative energy that can replace the presence of diesel fuel. Biodiesel is commonly made from vegetable oil. Vegetable oil and biodiesel belong to the large class of organic compounds are ester fatty acids. However, vegetable oils are triester 11 of fatty acids with glycerol, or triglycerides, while biodiesel or fatty acid methyl ester (FAME) is monoesters of fatty acids with methanol or ethanol by transesterification process (Ramadhas, *et al.* 2005; Hossain & Mazen, 2010).

The use of biodiesel from edible oil has a negative impact because it competes with its use as food consumption (Chuah, $et \ al. 2015$). Therefore, biodiesel

from non-edible oil is developed. One source of edible oil widely available in Indonesia is rubber seed. Rubber seed oil dries classified as type oil (drying oil) (Ketaren, 1986). The yield oil in rubber seed in the average 35-45 9 from different countries reported by Kittigowittana *et al* (2013).

Research in biodiesel from rubber seed oil has been developed, such as the type of catalyst, alcohol mass ratio, temperature, the concentration of catalyst (Widayat & Suherman, 2012; Abdulkadir, *et al.* 2014, Zamberi & Ani, 2016). The chemical characteristic of oil dependent on geographical origin (Kittigowittana, *et al.* 2013). In addition, the quality of the oil is affected by altitude and pedology. Rouas *et al.* (2016) reported

^{*} Corresponding author: pujilukitowati@yahoo.com



(1 tation: Salni, S, Hariani, P.L. and Marisa, H. (2017) Influence the Rubber Seed Type and Altitude on Characteristic of Seed, Oil and Biodiesel.. Int. Journal of Renewable Energy Development, 6(2), 157-163, https://doi.org/10.14710/ijred.6.2.157-163 P a g e | 158

that altitude affects the characteristic of virgin olive oil (<300, 300-600, >600 m). The other research reported that percentage of oil significan negative relation with altitude (Diza 12 ekan, *et al.* 2016).

Indonesia is the second largest rubber producer in the world. One of the provinces that have large farms is South Sumatra. In this area, rubber plants planted in all region altitude. Soil type in South Sumatera with acid pH suitable for rubber plant growth.

There are two types of rubber seed are superior and non-superior rubber seed (local rubber seeds). The farmers in Indonesia now use scraped seeds or seeds seedlings result of previous natural rubber plant. According to the Indonesian National Standard (SNI), superior rubber seeds are derived from selected vegetatively propagated clones such as grafting, cuttings, and tissue culture. The advantages of superior rubber seed include latex production of high quality and good properties of latex, ripe tapping robust growth 2 der 4 years old and a high biomass potential.

The fatty acid meth 4 ester (FAME) from rubber seed oil can be produced by two step reactions. The first step is esterification and the second step is transester 29 ation. The esterification reaction is required to reduce the content of free fatty 2 acids (Khazaai, *et al.* 2017; Bello & Otu, 2015). The rubber seed **17** has a high free fatty acid (FFA) (Ahmad, *et al.* 2014; Ramadhas, *et al.* 2005). The free fatty acids in the oil can react with a base catalyst which produces soap which complicate the process of separation of e**37** rs and glycerol (Marchetti & Errazu, 2008; Khazaai, *et al.* 2017). Ramadhas *et al.* (2005) reported that free fatty **5** ids are good for transesterification less than 2% or below 4 mg KOH/g oil.

This study investigates the characteristic of seed, oil content and methyl ester from a different type of rubber and altitude. The oil is extracted by n hexane as an extraction solvent. Transesterif 13 ion process of rubber seed oil after esterification using methanol and sodium hydroxide as catalyst The properties of methyl ester were analyzed according to the SNI and ASTM standard.

2. Materials and Methods

2.1 Rubber seeds

The local and superior rubber seeds collected from a plantation in Banyuasin District (18 m above sea level), Prabumulih District (176 m above sea level) and Lahat District (627 m above sea level) in South Sumatera province. The longitude and latitude of South Sumatera province at 5° 10'-1° 20' S and 101° 40' - 106° 30' N.

The superior rubber seeds namely PB-260. The rubber seed from rubber trees of the same age was given the following code: local rubber seed from Banyuasin district (BL), superior rubber seed from Banyuasin district (BS), local rubber seed from Prabumulih district (PL), superior rubber seed from Prabumulih district (PS), local rubber seed from Lahat district (LL) and superior rubber seed from Lahat district (LS).

2.2 Chemicals

The chemicals used in this study include methanol, sulfuric acid, sodium hydroxide and nhexane from Merck.

2.3 Analysis of rubber seed

The shell and kernels of rubber seeds separated by breaking. The kernels were dried under the sun for five days before crushed using a blender. The sample is dried in the oven about ± 5 h at 105°C. The powder of rubber seed is weighed and stored in a desicator. The rubber seeds analysis includes the weight of flour, moisture content, ash content, and oil content using recommended methods of the AOAC.

2.3 Oil extraction

Rubber seed powder of 100 g wrapped in paper filter is placed inside Soxhlet to extract. A total of 250 mL n-hexane is poured into Soxhlet. Extraction is done for 6 hours per cycle at 60° C. The extraction 36 cess is done three times. After extraction, the oil separated from the solvent by evaporation with a rotary evaporator at 60° C.

The rubber seed oil purification is done by deposition (settling), separation gumi (degumming) and bleaching. A total of 100 mL of rubber seed oil w 35 mixed with 0.2% w H₃PO₄ and stired for 15 minutes at a speed of 120 rpm and temperature of 50° C. After 30 minutes, the oil is separated from the sediment. The oil was added 0.1 g of activated carbon and stirred for 15 minutes then allowed to stand for 2 hours. Hereafter, the oil is filtered to separate the activated carbon. The oil was added some anhydrous Na₂SO₄ to adsorp the water content. Afterward, the oil has ready for analysis of rubber seed oil includes Free fatty acid (ASTM D664), viscosity (ASTM D4455), and fatty acid using GC-MS QP2010S Shimadzu.

2.4 Transesterification Process

Esterification is required before transesterification. The oil was esterified using sulfuric acid as a catalyst to reduce FFA to less than 2%. Methyl ester was prepared with mixture of 10 mL sulfuric acid 3_{6} (w/v) and 300 mL methanol 27 ere added 50 mL oil (ratio of methanol and oil = 6:1) (Ramadhas, *et al.* 2005; Ahmad *et al.* 2014). The mixture was heated at 60° C and stirred with at 120 rpm for 2 hours. Oil with reduced fatty acid content is separated from remaining methanol. The product is separated by rotary evaporator in a 70° C water bath.

Transesterification is conducted using NaOH as catalyst. The mixture of 0.5 % (b/v) NaOH 50 mL and

Int. Journal of Renewable Energy Development 6 (2) 2017: 157-163

Page | 159

450 mL of methanol (ratio of methanol and oil 9: 1) was added to 50 mL of oil. The mixture was heated for 2 hours at a temp 26 ture of 60°C. The product has two layers. The top layer is the methyl esters while the bottom is glycerol. The two layers are separated by separating funne 2 The methyl ester was neutralized with 0.05 M HCl, washed with distilled water and dried with anhydrous Na₂SO₄. The remaining methanol was evaporated with a rotary evaporator.

17 The methyl ester analysis includes cetane number (ASTM D-976), flash point (ASTM D-56), viscosity (ASTM D-445), carbon residue (ASTM D-189), specific gravity (ASTM D-1298), Moisture content (ASTM D-95), sediment (ASTM D-473) and distillation (ASTM D-38).

3. Result and Discussion

3.1 Characteristic of Rubber Seed

Rubber trees were planted generatively and vegetatively. The rubber seed planted generatively is called local rubber seed while vegetatively planted rubber seed is called superior rubber seeds. The use of superior rubber seeds to get more latex. In Indonesia, local rubber seed is more common because of cheap and practical.



Fig. 1 The growth of rubber tree from (a) superior rubber seed and (b) local rubber seed

Figure 1 shows the growth of rubber plants from superior rubber seed and local rubber seed. The trees from local rubber seed have a cylindrical rod, that is getting smaller towards the top and not the former linkage grafting found near the soil surface. In contrast, trees are derived from superior rubber seed have rod diameter up towards the top. There is a real former grafting linkage near the soil surface. The genetic properties affect plants growth (Sham, *et al.* 2014

Table 1 shows the characteristic of superior and local rubber seed. At the same weight, the superior rubber seed flour has less weight than local rubber seeds. The advantage of superior rubber seed is in the production of latex. The latex is the result from secondary metabolism while seed flour is from primary metabolism primer. Table 1 Characteristics of Rubber Sode

Parameter (%)	Superior rubber seed			Local rubber seed		
	BS	\mathbf{PS}	\mathbf{LS}	BL	PL	$\mathbf{L}\mathbf{L}$
Weight of Flour Moisture content Ash Content Oil content	38.6 3.01 2.89 43.5	41.3 2.90 2.77 44.2	50.3 3.34 3.11 40.5	59.0 3.91 4.32 38.8	59.0 3.71 4.02 39.9	53.0 4.02 4.43 36.8

Moisture content and ash content are important a rameter for establishing the relationship between rubber seed oil and its properties (Abdulkadir, *et al.* 2015). In this study, the moisture content and ash content of local rubber seed are greater than superior rubber seeds for all altitude. The characteristic of rubber seed from Prabumulih district showed the most excellent quality value of water content and ash content are small. Oil is expected to have a small moisture content to reduce hydrolysis reaction. From the table, we can see that the superior rubber seed.



Rubber seed oil is obtained by extraction using nhexane solvent. The yield (%) is parameters used to determine the amount of oil produced in the extraction

© IJRED – ISSN: 2252-4940, 15th July 2017, All rights reserved

(1tation: Salni, S, Hariani, P.L. and Marisa, H. (2017) Influence the Rubber Seed Type and Altitude on Characteristic of Seed, Oil and Biodiesel.. Int. Journal of Renewable Energy Development, 6(2), 157-163, https://doi.org/10.14710/ijred.6.2.157-163 P a g e | 160

process. The second showed that the percentage yield of superior rubber seed oil types is greater than the local rubber seeds for all altitude. The biggest amount of oil obtained from the superior rubber seed at Prabumulih district in 176 m above sea level of 44.2 %.

The area suitable for growing rubber is in the zone between 15° LS and 15° LU. The rubber plant grows optimally in the lowlands between 0-200 meters above sea level and at a temperature $25-35^{\circ}$ C. An altitude more than 600 m above sea level is less suitable for rubber plant growth (Setyamidjaja, 1993). In this study, the oil content for Lahat district have the less oil content. The altitude more than 600 m above sea level. The tropics have a similar climate, but the difference in altitude causes differences in temperature, humidity and rainfall. The higher of elevation impacts the lower temperature and the higher the humidity. This it inhibit the growth of rubber plants (Andrian, *et al.* 2014).

Table 2

3.1 Characteristic of Rubber Seed Oil

Figure 2 shows the superior and local rubber seed oil and biodiesel produced. The volle of superior rubber seed is smaller than the local rubber seed. The physical and chemical characteristic of rubber seed oil are shown in Table 2. The parameters analyzed on rubber seed oil include free fatty acids, viscosity, and fatty acid composition. From the result, the FFA of superior rubber seed oil is 13.897-15.494 % while local rubber seed oil 4 as less FFA of 9.786-10.399 %. Both rubber seed oil has high content of 4 FA, therefore it is required to perform esterification to reduce FFA. The high content of FFA also produced from rubber seed oil obtained by mechanical press, which is 10.39-16.48 % (Widayat & Suherman, 2012).

Parameter	Sup	erior rubł	per seed	Local rubber seed		
	BS	PS	LS	BL	PL	$\mathbf{L}\mathbf{L}$
Free fatty acid (%)	15.494	14.207	13.897	10.094	10.399	9.786
Viscosity (Cst)	41.873	41.790	41.458	35.526	35.066	34.115
Fatty acid (%)						
- Pentadecanoic acid	12.01	12.56	5.00	12.15	11.74	5.18
- Linoleic acid	57.42	55.15	31.72	57.44	57.86	25.55
- Octadecanoid acid	19.26	22.37	7.28	19.12	20.59	54.26
- Stearic acid	9.11	8.93	28.38	9.85	8.55	
- Palmitic acid		0.59	18.93	-		
- Pentanoic acid		-	-	-		12.48
- others	2.20	0.40	8.69	1.44	1.26	2.53

Viscosity is an intrinsic fluid property that shows resistance to the flow of fluid. The viscosity of superior rubber seed oil from different altitude with the value of 41.873, 41.790 and 41.458 Cst are greater than from local rubber seed oil with the value of 35.526, 35,07 and 34.115 cSt. Another study shows that viscosity of rubber seed oil is 66.2 (Ramadhas, *et al.* 2005) and 34.69 cSt (Satyanarayana & Muraleedharan, 2010), respectively.

The determination of fatty acid composition using GC-MS showed that rubber seed oil consists mainly of linoleic acid except local rubber seed oil from Lahat district (LL) 22 th the large percentage of 54.26 % octadecanoic acid. The difference of fatty acid content in the rubber seed oil 34 be caused by different types of rubber and altitude. The composition and percentage of fatty acids in seed oil of local and superior rubber seed on Banyuasin and Prabumulih district not significantly different. Both areas have almost the same altitude less than 200 above sea level.

The linoleic acid classified as unsaturated fatty acids with the atomic number 18 and two double bonds. The same result reported Pianthong & Prachasanti (2009); Yousif *et al.* (2013), Gimbun *et al.* (2013), Bello & Otu (2015) and Awulu *et al.* (2015) that the main content of rubber seed oil is linoleic acid with percentage of 41.38, 36.31, 20.07, 37.7 and 37.5 %, respectively. The results showed that the fatty acids from local and superior rubber seeds in Lahat district with altitude more than 60 12 h have a different composition than others. The chromatogram of fatty acid from superior rubber seed and local rubber seed oil presented in figure 3.

3.1 Biodiesel from Superior Rubber Seed Oil and Local Rubber seed oil

Synthesis of biodiesel perfor 21 with 2 steps, the first step is esterification using acid catalyst and the second step is transesterification using a based catalys 25 The aims of esterification reaction are to reduce free fatty acids and water content. The pite nce of water in the biodiesel cause corrosion in the combustion chamber when used as fuel. In addition, high FFA cause low production of biodiesel (Zamberri & Ani, 2016).



Fig. 3 GC-Chromatogram of fatty acid from rubber seed oil

The esterification process is carried out using H₂SO₄

Page | 161

as catalyst in a closed condition resulting in a very significant reduction of FFA. The high FFA content contribute 24 to higher saponification and low yield biodiesel. In this study, the content of free fatty acids of superior rubber seed oil is reduced from 13.897-15.494 mg/g to 1.104-2.017 mg/g while local rubber seed 15 is reduced from 9.786-10.399 to 0.598-0.630 mg/g. Figure 4 shows the FFA of rubber seed oil for all type and altitude. The larger volume of oil, the greater value of FFA. The FFA value in superior rubber seed oil is bigger than local rubber seed but altitude does not affect to FFA value. There are significant different for all FFA value in rubber seed oil before and after esterification.



Fig. 4 The FFA of rubber seed oil before and after esterification

Table 3 shows the characteristic of biodiesel fr(2) local and superior rubber seed oil from all altitude by transesterification using methanol and NaOH as catalyst. Analysis of methyl ester product includes cetane index, flash point, kinematic viscosity, carno residue, moisture content, water and sediment content and destilation.

The value of cetane index depends on distributed and long fatty acid (Laza & Bereczky, 2010). The methyl ester of superior rubber seed from Prabumulih and Banyuasin District have the highest value cetane index and qualified to minimum standard of biodiesel according to the SNI. The both of methyl ester has a similarity that is dominated by unsaturated fatty acids is 123 eic acid.

Flash point is the lowest temperature of biodiesel where oil vapor and air mixture to be burned. The standard value of the minimum flash point (SNI 7182) is 100°C. In this study, the highest flash point is the biodiesel for superior rubber seed from Banyuasin and Prabumulih district and all of the methyl ester according to the SNI. The other research shows methyl ester from rubber seed has a different flash point of 185, 194 and 237 °C (Ibrahim & Pillai, 2011; Ramadhas, *et al.* 2005, Satyanarayana & Muraleedharan, 2010).

 $\ensuremath{\mathbb{C}}$ IJRED – ISSN: 2252-4940, 15th July 2017, All rights reserved

(1tation: Salni, S, Hariani, P.L. and Marisa, H. (2017) Influence the Rubber Seed Type and Altitude on Characteristic of Seed, Oil and Biodiesel.. Int. Journal of Renewable Energy Development, 6(2), 157-163, https://doi.org/10.14710/ijred.6.2.157-163 P a g e | 162

Table 3

Characteristics of Biodiesel

Parameter of biodiesel	Superior rubber seed		Local rubber seed			SNI 7182	ASTM D6751- 02	
	BS	PS	\mathbf{LS}	BL	PL	LL		
artane Index	51.23	53.03	41.23	48.25	50.34	40.98	51 Min	$47 \operatorname{Min}$
Flash point (°C)	179	180	168	162	161	156	100 Min	
Kinematic Viscosity, 40°C (cSt)	5.67	5.69	4.89	4.68	4.23	3.95	2.3-6.0	1.9-6.0
Carbon residue (%)	0.043	0.048	0.057	0.049	0.053	0.061	$0.05 \mathrm{Max}$	$0.05 \mathrm{Max}$
Density (kg/m ³)	878.9	877.2	875.6	853.1	8571.6	855.8	850 32	-
Moisture content (mg/L)	482	477	496	495	497	501	500 Max	-
Water and Sediment content (%)	0.026	0.027	0.029	0.025	0.026	0.026	$0.05 \mathrm{Max}$	
Distillation (°C)	345	351	375	341	352	382	360 Max	360 Max

The viscosity is an important test in the biodiesel. The operation of fuel injection equipment influenced by viscosity (Bello & Otu, 2015). The viscosity of biodiesel from all type and altitude is in the range of 3.95-5.89 cSt. The high viscosity of the biodiesel was obtained from superior rubber seed file Banyuasin and Prabumulih district. This is correlated with the number of carbon atoms and the double bonds carbon of the fatty acids. The more number of carbon atoms and the double bonds carbon will result in greater viscosity.

The sediment should be avoided to prevent build up that causes damage to the diesel engine. In this study, carbon residue of superior and local rubber seed from Lahat District are above the standard carbon residue of biodiesel of maximum 0.05 % (SNI 7182; ASTM D6751-02).

Some research reported that rubber seed oil has high density, after transesterification process to be reduced (Bello & Otu, 2015). The standard of density in the range 850-890 kg/m³. This result shows that density of biodiesel from superior rubber seed is greater than local rubber seed for all altitude and all of methyl ester according to SNI.

The moisture content can cause imperfect combustion, furthermore water is in contact wight sulfur oxide will cause corrosion of the metals in the combustion chamber. The maximum value of the biodiesel according to ASTM D6751-02 is 500 mg/L. In this study only methyl ester from local rubber seed in Lahat district that does not qualify. The main component of rubber seed oil of decanoid acid which is different with the other rubber seed oils.

In this study, sediment analysis shows that biodiesel in all types and altitude are qualified the requirements which is less than 0.05 %. The aim of sediment analysis to investigate the presence of particles, such as sand, dirt, or compounds that dissolve and including suspension and metal. Sediment is corrosive, which would cause air pollution and lower the cetane number of a fuel oil. Sediment can also poison the catalyst.

The 40 e of a liquid turns to gas plays an important role in mixture of air and diesel fuel at the time of ignition in diesel engine combustion chamber. The distillation of biodiesel of superior and local rubber seed in Lahat which are not qualified the maximum distillation of 360 °C.

7. Conclusion

The rubber plants can be planted by selected clones (superior rubber seed) and seeds seedlings (local rubber seed). The type of rubber 14 eds of the rubber trees planted in South Sumatra affect the quality of rubber seed, oil, and methyl ester. The altitude does not have a positive effe 20 n the quality of rubber seed, oil, and methyl ester. The methyl ester product from superior rubber seed at Banyuasin District (18 m above sea level) and Prabumulih District (176 m above sea level) have similar quality and according to the standard of biodiesel (SNI 7182 and ASTM D6751-02).

Acknowledgments

We are grateful to Sriwijaya University for funding research No. <u>3</u>92/UN9.3.1/LT/2016, Department of Biology and Department of Chemistry, Faculty of Mathematics and Natural Science for facilities research.

References

- Abdulkadir, B.A., Yoshimitsu, U., Anita, R., Noridah, Bt, O., Katsuki, K., & Takami, K. (2015)Production of Biodiesel from Rubber Seeds (*Hevea Brasiliensis*) by In Situ Transesterification Method. Journal of the Japan Institute of Energy, 94,763-768
- Andrian, Supriadi., & Purba, M. (2014) The Effect of Elevation and Slope on Rubber (*Hevea brasiliensis* Muell. Arg.) Production in PTPN III Hapesong Farm of South Tapanuli. Jurnal Online Agroteknologi, 2(3), 981:989
- Ahmad, J., Suzana, Y., Awais, B., & Ruzaimah, N.M.K. (2014) Biodiesel production from the High Free Fatty Acid "Hevea Brasiliensis" and Fuel Properties Characterization. Applied Mechanics and Materials, 625, 897-900
- Awulu¹, J.O., Ogbehb, G.O., & Asawac. (2015) Comparative Analysis of Biodiesels from Calabash and Rubber Seeds Oils.

International Journal of Renewable Energy Development, 4(2), 131-136

- Bello, E.I., & Otu, F. (2015) Physicochemical Properties of Rubber (Hevea Brasiliensis) Seed Oil, Its Biodiesel, and Blends with Diesel. British Journal of Applied Science and Technology, 6(3), 261-275
- Chuah, L.F., Suzana, Y., Abdul, R.A.A., Jiri, J.K., Awais, B., & Mohd, Z.A. (2015) Influence of Fatty Acids Content in Non-Edible Oil for Biodiesel Properties. *Clean Techn Environ Policy*, 1-10
- Dizajeyekan, Y.I., Ahmad, R.H., & Tohid, E.G. (2016) Regional Altitude and Soil Physicochemical Factors Influence the Essential Oil of *Thymus pubescens* (Lamiales: Lamiaceae). J. Biol. Environ. Sci., 10(29), 45-51
- Gimbun, J., Shahid, A., Chitra, C.S.C.K., Liyana, A.S., Nurul, H.M.G., Chin, K.C., & Said, N. (2012) Biodiesel Production from Rubber Seed Oil Using A Limestone Based Catalyst. Advances in Materials Physics and Chemistry, 2, 138-141
- Hossain, A.B.M.S., & Mazen, M.A. (2010) Effects of Catalyst Types and Concentrations on Biodiesel Production from Waste Soybean Oil Biomass as Renewable Energy and Environmental Recycling Process. Australian Journal of Crop Science, 4(7), 550-555
- Ibrahim, A.M., & Pillai, B.C. (2011) Optimization of Process Parameters for Biodiesel Extraction from Rubber Seed Oil Using Central Composite Design. International Journal of Production Technology and Management Research, 2(1), 2229-3140
- Ikwuagwu, O.E., Ononogbu, I.C., & Njoku, O.U. (2000) Production of Biodiesel Using Rubber [(Hevea Brasiliensis(Kunth. Muell)] Seed Oil. Industrial Crops and Products, 12, 57-62
- Ketaren, S. (1986) Pengantar Teknologi Minyak dan Lemak Pangan, UI Press, Jakarta
- Khazaai, S.N.M., Gaanty, P.M., Mohd, H.A.R., Mashitah, M.Y., & Yukihiko, M. (2017) Review on Methyl Ester Production from Indible Rubber Seed Oil under Various Catalyst. *Industrial Crops and Products*, 97, 191-195
- Kittigowittana, k., Wongsakul, S., Krisdaphong, P., jimtaisong, A., & Saewan, N. (2013) Fatty Acid Composition and Biological Activities of Seed Oil from Rubber (*Hevea* Brasiliensis) Cultivar RRIM 600. International Journal of Applied Research in Natural Products, 6(2), 1-7
- Kouzu, M., Kasuno, T., Tajika, M., Yamanaka, S. & Hidaka, J. (2008) Active Phase of Calcium Oxide used as Solid Base Catalyst for Transesterification of Soybean Oil with Refluxing Methanol. Applied Catalysis, 334(1-2), 357-365

- Laza, T., & Bereczky, C. (2010) Basic Fuel Properties of Rapeseed Oil-Higher Alcohol Blends. *Fuel*, 20(2), 803-810
- Marchetti, J.M., and Errazu, A.F. (2008) Esterification of Free Fatty Acids using Sulfuric Acid as Catalyst in the Presence of Triglycerides. *Biomass and Bioenergy*, 32(9), 892-895
- Pianthong, K., & Prachasanti, T. (2009) Production of Biodiesel Seed Oil and Its Effects to Engine Performances. International Conference on Energy Security and Climate Change: Problems & Issues in GMS.
- Ramadhas, A.S., Jayaraj, S., & Muraleedharan, C. (2005) Biodiesel Production from High FFA Rubber Seed Oil. Fuel, 84, 335-340
- Satyanarayana, M., & Muraleedharan, C. (2010) Methyl ester Production from Rubberseed Oil using Two-Step Pretreatment Process. International Journal Of Green Energy, 7(1), 84–90.
- Shams, M., Mahdi, R., Sasan, Z.E., Ehsan, Z.E., Atilla, D., & Ertan, Y. (2016) Effects of Climatic Factors on the Quantity of Essential Oil and Dry Matter Yield of Coriander (Coriandrum satioum L.). Indian Journal of Science and Technology, 9(6), 1-4
- Setyamidjaja, D. (1993) Karet: Budidaya dan Pengolahan. Kanisius. Yogyakarta
- Rouas, S., Mohammed, R., Abdrraouf, E.A., Lahoussaine, B., Drissia, J.I., Abdelaziz, S., & Nadia, M. (2016) Effect of Geographical Conditions (Altitude and pedology) and Age of Olive Plantations on the Typicality of Olive Oil In Moulay Driss Zarhoun. *Mediterranean Journal of Biosciences*, 1(3), 128-137
- Widayat, Agam, D.K.W., & Hadiyanto. (2013) Study on Production Process of Biodiesel from Rubber Seed (*Hevea Brasiliensis*)by In Situ (Trans)esterification Method with Acid Catalyst. International Conference on Sustainable Energy Engineering and Application, *Energy Procedia*, 32, 64-73
- Widayat., W & Suherman, S. (2012) Biodiesel production from Rubber seed Oil via Esterification Process. International Journal of Renewable Energy Development, 192), 57-60
- Yousif, E., Bashar, A., Hanan, I., Jumat, S., & Nadia, S. (2013) Rubber Seed Oil Properties, Authentication and Quality Assessment Using (Chloroform: Methanol) as Solvent. *Journal* of Al-Nahrain University, 16(3), 1-6
- Zamberi, M.M., & Ani, F.N. (2016) Biodiesel Production from High FFA Rubber Seed Oil Using Waste Cockles. ARPN Journal of Engineering and Applied Sciences, 11(12), 7782-7787

Influence of the Rubber Seed Type and Altitude on Characteristic of Seed, Oil and Biodiesel

ORIGIN	ALITY REPORT				
SIMILA	5% ARITY INDEX	3% INTERNET SOURCES	10% PUBLICATIONS	14% STUDENT PA	APERS
PRIMAF	RY SOURCES				
1	Muhamn Kusword Penamb Metanol dan Teki Publication	nad Fahmi Hakim b. "Pengaruh Mete ahan Pengisi pac Fuel Cell", JRST hologi), 2018	n, Tutuk Djoko ode Sulfonasi la Membran D (Jurnal Riset 3	dan irect Sains	1%
2	Submitte Student Paper	ed to Universiti Te	eknologi Petroi	าลร	1%
3	Submitte Pakistan Student Paper	ed to Higher Educ	ation Commis	sion	1%
4	Submitte Student Paper	ed to Institute of G	Graduate Studi	es, UiTM	1%
5	Submitte Universit Student Paper	ed to Jawaharlal N ay Anantapur	Nehru Technol	ogical	1%
6	Alexandı Ouellet-F	ra Charles, Wahio Plamondon. "Cas	d Maref, Clauc e study of the	liane M. upgrade	1%

of an existing office building for low energy

consumption and low carbon emissions",

Energy and Buildings, 2018

Publication

7	Submitted to Universiti Teknologi Malaysia	1%
8	ro.ecu.edu.au Internet Source	1%
9	Submitted to 7996 Student Paper	1%
10	ic3pe.chemistry.uii.ac.id	<1%
11	Submitted to Chulalongkorn University Student Paper	<1%
12	Lai Fatt Chuah, Awais Bokhari, Suzana Yusup, Jiří Jaromír Klemeš, Bawadi Abdullah, Majid Majeed Akbar. "Optimisation and Kinetic Studies of Acid Esterification of High Free Fatty Acid Rubber Seed Oil", Arabian Journal for Science and Engineering, 2015 Publication	<1%
13	pscipub.com Internet Source	< 1 %
14	Wendy Pei Qin Ng, Mook Tzeng Lim, Sohibatul	<1%

Muizzah bt Mohamad Izhar, Hon Loong Lam, Suzana Yusup. "Overview on economics and

technology development of rubber seed utilisation in Southeast Asia", Clean Technologies and Environmental Policy, 2013

Publication

15	Submitted to iGroup Student Paper	<1 %
16	Submitted to Federal University of Technology Student Paper	<1%
17	Pereira, R.G "Exhaust emissions and electric energy generation in a stationary engine using blends of diesel and soybean biodiesel", Renewable Energy, 200711 Publication	<1%

- Eugene D. Nikitin, Pavel A. Pavlov, Alexander P. Popov. "Critical temperatures and pressures of some alkanoic acids (C2 to C22) using the pulse-heating method", Fluid Phase Equilibria, 2001 Publication
- 19 Felix E. Okieimen. "Epoxidation and hydroxlation of rubber seed oil: one-pot multistep reactions", European Journal of Lipid Science and Technology, 05/2005 Publication
- 20 M. Satyanarayana, C. Muraleedharan. "Methyl Ester Production from Rubber Seed oil Using Two-Step Pretreatment Process", International

<1%

<1%

<1%

Journal	of	Green	Energy,	2010
---------	----	-------	---------	------

Publication

21	Submitted to University of Bath Student Paper	<1%
22	Submitted to Universiti Malaysia Kelantan Student Paper	<1%
23	Submitted to Universiti Malaysia Pahang Student Paper	<1%
24	Baiju, B., L. M. Das, and M. K. G. Babu. "The Effect of Using High FFA Rubber Seed Based Biodiesel With Cold and Hot EGR on Performance and Emissions of a CI Engine", ASME 2008 Internal Combustion Engine Division Spring Technical Conference, 2008. Publication	<1%
25	biodieseleducation.org	<1%
26	Submitted to Universiti Teknologi MARA Student Paper	<1%
27	Huong Trinh, Suzana Yusup, Yoshimitsu Uemura. "Optimization and kinetic study of ultrasonic assisted esterification process from rubber seed oil", Bioresource Technology, 2018 Publication	<1%
28	gjournals.org	<1%

- A. Bulent, Mudhafer Abdullah, Mohammad <1% 29 Fereidouni. "Chapter 2 Soybeans Processing for Biodiesel Production", IntechOpen, 2011 Publication
- Widayat, Hantoro Satriadi, Aji Baharsyah, 30 Supriyandi. "Biodiesel production from jatropha curcas oil and palm oil by using undirect ultrasonic assisted", 2016 International **Conference on Sustainable Energy Engineering** and Application (ICSEEA), 2016 Publication
- Olusegun Peter Akinyemi, Joseph Denis 31 Udonne, Vincent Enontiemonria Efeovbokhan, Ayodeji Ayodele Ayoola. "A study on the use of plant seed oils, triethanolamine and xylene as flow improvers of Nigerian waxy crude oil", Journal of Applied Research and Technology, 2016 Publication

32	Submitted to Universiti Malaysia Terengganu	<1
02	UMT	
	Student Paper	



33

34

S. Sakthivel, Sudipta Halder, P. D. Gupta. "Influence of Co-Solvent on the Production of <1%

<1%

<1%

<1%

Biodiesel in Batch and Continuous Process", International Journal of Green Energy, 2013

35

Vinod Babu Marri, Madhu Murthy Kotha, Amba Prasad Rao Gaddale. "Production process optimisation of methyl esters (biodiesel) using response surface methodology ", International Journal of Ambient Energy, 2020

Publication

ijetsr.com <1% 36 Internet Source <1% Mahanum Mohd Zamberi, Farid Nasir Ani. 37 "chapter 5 Non-Edible Oil Biodiesel Production via Microwave Irradiation Technologies Using Waste-Heterogeneous Catalyst Derived From Natural Calcium Oxide", IGI Global, 2020 Publication www.thaiscience.info <1% 38 Internet Source <**1**% Mariana, Rina Rifqie, Titi Mutiara Kirana, and 39 Laily Hidayati. "Analysis on the Quality Change of Tempeh, Catfish and Fried Chicken as the Effect of the Repetitive Used Cooking Oil",

Journal of Food Research, 2014. Publication



<1%

41 Banani Ridha, Abderrabba Manef, Bezzarga Mounir. "Pretreatment of waste frying oil with high levels of free fatty acids for biodiesel production", 2014 5th International Renewable Energy Congress (IREC), 2014 <1%

<1%

Publication



Exclude quotes	Off	Exclude matches	Off
Exclude bibliography	On		