PAPER • OPEN ACCESS

Hydrodynamic Analysis of Hydrolysis of the Rice Husk Cellulose by Using CFD Modeling

To cite this article: N Novia et al 2019 IOP Conf. Ser.: Mater. Sci. Eng. 543 012046

View the article online for updates and enhancements.



IOP ebooks[™]

Bringing you innovative digital publishing with leading voices to create your essential collection of books in STEM research.

Start exploring the collection - download the first chapter of every title for free.

Hydrodynamic Analysis of Hydrolysis of the Rice Husk **Cellulose by Using CFD Modeling**

N Novia, L Cundari, A M Jannah, M K Haphsari and M Zulfani

Chemical Engineering Department, Faculty of Engineering, Universitas Sriwijaya, Jl. Raya Indralaya-Prabumulih KM. 32 Indralaya Ogan Ilir (OI), Sumatera Selatan, Indonesia 30662

E-mail: novia@ft.unsri.ac.id

Abstract. The importance of the rule and the demand of glucose trigger the seeking of the alternative materials to produce glucose. One of the alternatives used is the utilization of biomass such as the rice husk to produce glucose. Rice husk is the agricultural residue whose availability is very abundant. In this research, rice husk contained cellulose (42.2 %), hemicellulose (17.04 %), and lignin (20.46 %). First step to produce the glucose from rice husk was pretreatment stages (Soaking in Aqueous Ammonia pretreatment and Acid pretreatment). Furthermore it was followed by the acid hydrolysis step by using dilute H₂SO₄ solution. The concentration of H₂SO₄ used in this work was 1, 2, and 3 N with the various hydrolysis times of 30, 60, 90, 120, and 150 min. The result showed that increasing of hydrolysis time slightly increased glucose concentration. The highest glucose concentration was about 21.51% at H₂SO₄ concentration of 2 N and the hydrolysis time of 150 min, CFD modeling (ANSYS Fluent 16) was performed to investigate the hydrodynamic phenomena during hydrolysis. The hydrodynamic analysis showed that the best mixing occurred at H₂SO₄ concentration of 2 N for 150 min. It is a good agreement with the experimental finding.

1. Introduction

Rice husk is agricultural residue whose availability is very abundant. It can produce glucose because it contains lignocellulose structure. The steps to produce glucose from rice husk are pretreatment and hydrolysis. Pretreatment aims to damage the lignin bond and break down a structure of cellulose crystal easily into glucose. Immersion in an ammonia solution is performed to reduce the amount of lignin and increase cellulose porosity, while the treatment using dilute sulphuric acid is done to increase cellulose porosity and help partially hydrolyse cellulose. Cellulose can be hydrolysed into glucose using aqueous media and assisted with acid or enzyme catalysts. The imperfection of the hydrolysis process can produce cellulose disaccharides. While the process of hydrolysis that runs perfectly will produce cellulose monomer in the form of glucose.

The advantage of chemical hydrolysis process is low cost. The price of chemicals is cheaper than enzymes. In addition, the enzymatically hydrolysis process takes several days while chemical hydrolysis requires relatively faster time [1]. Alternatively, dilute acids can be used to break the polymer chains of cellulose and hemicellulose. In the acid hydrolysis method, lignocellulose biomass is exposed to the acid at a given temperature and pressure for a certain time and produces a sugar monomer of cellulose and hemicellulose polymers. Sulphuric acid is the most widely studied acid and is used for acid hydrolysis [1]. Cellulose can be chemically hydrolysed using H₂SO₄ solution.

Content from this work may be used under the terms of the Creative Commons Attribution 3.0 licence. Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI. Published under licence by IOP Publishing Ltd 1

1st International Symposium of Indonesian Chemical Engineering (ISIChem) 2018IOP PublishingIOP Conf. Series: Materials Science and Engineering 543 (2019) 012046doi:10.1088/1757-899X/543/1/012046

One indicator of the pretreatment effectiveness is the reduction of lignin during process. Pretreatment of the biomass results in the degradation of cellulose and hemicellulose. Effect of hydrothermal pretreatment of date palm leaflets and vine shoots on lignin was investigated by other researchers [2,3]. However they used a high temperature condition. Chemical pre-treatment using liquid ammonia and aqueous sodium hydroxide (NaOH) are recognized to change the cellulose crystalline structure and effect on enzymatic digestibility [4]. Previous authors [5], performed NaOH-dilute acid pretreatment to remove lignin in rice husk. The use of sulphuric acid is also required in the neutralization process which produces very large amounts of gypsum or lime waste and can pollute the environment [1]. Ammonia pretreatment eliminates lignin by cutting C–O–C bonds in lignin [6]. The effect of aqueous ammonia and dilute acid, on the chemical compositions, cellulose crystallinity, morphologic change, and enzymatic hydrolysis of bamboo was studied by previous researcher [7]. Therefore, this research focused on the soaking in aqueous ammonia (SAA) pretreatment and dilutes sulphuric acid of rice husk. Furthermore, hydrolysis was carried out using sulphuric acid (H₂SO₄) with various concentrations. The hydrolysis reaction between water and cellulose was catalysed by acid so that the reaction proceeded quickly and produced faster glucose.

Some studies have tried to describe the hydrodynamic phenomena in pretreatment [8] and enzymatically hydrolysis process [9–11] by using a design and CFD modelling. However this work used a different kind of reactor which is a laboratory spherical reactor. A perfect mixing process was required to obtain optimal glucose levels. Therefore, this study applied CFD modelling (ANSYS Fluent 16) to produce hydrodynamic mixing process in acid hydrolysis.

2. Materials and methods

2.1. Raw Material Preparation

The rice husk was dried under the sun for ± 1 day. Its size was reduced to 35 meshes. Then, the composition of cellulose, hemicellulose and lignin was analysed by using a Chesson method [12]. Scanning electron microscope (SEM) micrographs of cross section rice husk of were carried out by a SEM-EDX microscope Phenom Pro X.

2.2. Pretreatment Raw materials

Dried rice husk of about 40 g was put into an erlenmeyer of 300 ml and soaked in 15 % (w/v) aqueous ammonia of 160 ml at 600 °C for 5 h. The filtrate was separated from the residue by a vacuum pump. Then the residue was washed with distilled water. Pretreated sample was fed to a glass bottle, and then added 135 ml of H_2SO_4 (0.18 N). It was stirred evenly for 1 min. Then it was heated in the oven at 160 °C for 35 min. It was cooled in room temperature and filtered by vacuum pump. Pretreated sample was analysed by using a Chesson method [12].. Scanning electron microscope (SEM) micrographs of cross section pretreated rice husk were carried out by a SEM-EDX microscope Phenom Pro X.

2.3. Hydrolysis process

20 g of pretreated sample and 200 ml of H_2SO_4 (1N) were inserted into three neck flask. They were hydrolysed at a temperature of 100 °C, a speed of 200 rpm for 30 min. Repetition was performed at variable H_2SO_4 of 2 N, and 3 N for 60 to 150 min. The contents of glucose were determined using the standard procedures according to Luff-Schoorl [13].

2.4. Numerical CFD Simulation

CFD modelling of Hydrodynamic of Hydrolysis of pretreated rice husk was referred by previous authors [14,15]. ANSYS Fluent 16 with a finite volume method was used to solve the general partial differential equations that illustrate fluid flow, momentum and mass transport. The geometry of hydrolysis reactor was shown in figure 1a and 1b. The reactor had a diameter of 0.2 m. Initially, a pretreated sample was put at the reactor bottom to a level above the impeller, and then sulphuric acid was injected to the rest of the reactor. The volume fraction of 10 % of pretreated rice husk in the slurry entered to the reactor

1st International Symposium of Indonesian Chemical Engineering (ISIChem) 2018	IOP Publishing
IOP Conf. Series: Materials Science and Engineering 543 (2019) 012046 doi:10.1088/1757-8	99X/543/1/012046

of, with the average diameter of 50 μ m. The reactor had the temperature of 100 °C for 30 min and speed of 200 rpm. A reactor schematic and the initial position of slurry solution were described in figure 1c. There were three fluid zones within the domain. The first zone represented the impeller zone; the region where the cellulose slurry was initially posited; the rest of reactor where H₂SO₄ solution was fed. A calculation was started by using the initial assumption similar to the specified volume fractions. The pretreatment process was simulated for various hydrolysis time for 60 to 150 min. A pretreated rice husk entered the reactor in the form of slurry. The simulation was operated in unsteady state conditions with time step sizes equal to 0.1 s. The Eulerian-Eulerian Multiphase flow and standard k– ϵ model was applied in all cases for accounting the turbulence effects. Hydrodynamic analysis of the hydrolysis reactor was obtained from 5 unsteady state simulations (30, 60, 90, 120, and 150 min) at different sulphuric acid concentrations of 1N, 2N and 3 N.



Figure 1. (a) 3-Dimensional geometry of reactor; (b) 2-Dimensional geometry of reactor; (c) initial condition of slurry.

3. Results and discussion

3.1. Morphological of the Rice Husk Structure

To ensure the successful of SAA-dilute acid pretreatment process, it is crucial to see a morphological of the rice husk structure. Chemically pretreated rice husk was analysed by SEM to investigate the change in rice husk before and after the pretreatment. Figure 2 illustrates the morphology of the rice husk structure before pretreatment (a), after SAA (b), after SAA-acid pretreatment (c). It is observed that a morphological of rice husk (figure 2a) changed to fibrous clusters (figure 2b). It is described by SEM that there was a changing in a microstructure of rice husk. This is due to more lignin was removed by SAA pretreatment. Significant lignin was also reduced after SAA-acid pretreatment (figure 2c). It can be concluded that the pretreatment of rice husk led it much more porous to be hydrolysed. The elimination of lignin and changing of its structure enhanced the degradation of cellulose and hemicellulose from biomass. In the SAA-acid pretreatment, a major part of the amorphous material (glucan) was eliminated or the crystalline structure was destroyed by swelling.



Figure 2. The morphology of the rice husk structure: (a) before pretreatment: (b) after SAA pretreatment; (c) after SAA-acid pretreatment. Magnification of images given in figure 2a, 2b and 2c are 1000X, 2000X and 3000X.

3.2. Effect of Hydrolysis Time on Glucose Levels at Various Concentrations of H₂SO₄

Figure 3 describes the effect of hydrolysis time on glucose levels at Various Concentrations of H2SO4. It is shown that the longer hydrolysis times produced the higher of glucose level. It illustrates that the length of reaction time between cellulose and water affected the amount of glucose. This is due to the longer of the reaction time caused more collisions between cellulose and water. In this study the optimum hydrolysis reaction time is 150 min. The higher concentration of acids enhanced the activation energy. The highest glucose level was about 21.51% at the H₂SO₄ concentration of 3 N for 150 min.





3.3. Hydrodynamic Analysis of Cellulose Volume Fraction during Hydrolysis at H₂SO₄ Concentration of 1N

Figure 4 shows cellulose volume fraction during hydrolysis at H_2SO_4 concentration of 1N. It presents the volume fraction of cellulose, predicted by the CFD simulation of this research. The red colour indicates the high volume fraction of cellulose. The blue colour shows the low volume fraction of cellulose. The distribution of cellulose volume fraction was heterogeneous and mainly distributed about the middle. This non homogeneity was caused by the circular liquid flow under the solid-liquid interaction.



Figure 4. Hydrodynamic analysis of cellulose volume fraction during hydrolysis process at H₂SO₄ 1N: (a) 30 min; (b) 60 min; (c) 90 min; (d)120 min; (e)150 min.

3.4. Hydrodynamic Analysis of Cellulose Volume Fraction during Hydrolysis at H_2SO_4 Concentration of 2N

Figure 5 describes the pattern of mixing motion in cellulose hydrolysis process at the H_2SO_4 concentration of 2 N. The predicted cellulose volume fraction distribution illustrates a higher cellulose concentration near the wall and absence of cellulose at the central of reactor. The benefit of the static mixers is that they avoid sedimentation of solids through modifications in reactor geometry. It is shown that the perfect mixing patterns tended to be constant. This is due to the mixing affected the hydrolysis process. Perfect mixing produced the higher glucose.



Figure 5. Hydrodynamic analysis of cellulose volume fraction during hydrolysis process at H₂SO₄ 2N: (a) 30 min; (b) 60 min; (c) 90 min; (d) 120 min; (e) 150 min.

It can be seen from figure 5 that the longer time of hydrolysis time led more cellulose degrades to glucose. It is reasonable with the experimental test. It can be concluded that the optimum condition of hydrolysis process was obtained at H_2SO_4 concentration of 2N for 150 min.

3.5. Hydrodynamic Analysis of Cellulose Volume Fraction during Hydrolysis at H₂SO₄ Concentration of 3N

Figure 6 presents the flow field of cellulose volume fraction at the H_2SO_4 concentration of 3N. The distribution of cellulose volume fraction was heterogeneous and mainly distributed about the middle. This non homogeneity was caused by the circular liquid flow under the solid-liquid interaction.



Figure 6. Hydrodynamic Analysis of Cellulose Volume Fraction during Hydrolysis Process at H_2SO_4 3N: (a) 30 min; (b) 60 min; (c) 90 min; (d) 120 min; (e) 150 min.

4. Conclusion

It can be concluded that a morphological of rice husk changed to fibrous clusters after SAA pretreatment. Significant lignin was also removed after SAA-dilute acid pretreatment. The pretreatment of rice husk led it much more porous to be hydrolyzed. The longer hydrolysis time of rice husk cellulose increased glucose level significantly. The optimum concentration of H_2SO_4 produced the highest glucose level of 21.51% at H_2SO_4 concentration of 2N for 150 min. Through hydrodynamic analysis with CFD modeling, cellulose hydrolysis with H_2SO_4 concentration of 2N for 150 min had the best mixing distribution pattern for almost every time variable. It is reasonable with the experimental test. The model and results presented in this study are valuable for the application of CFD model to calculate the flow of biomass suspensions in spherical reactors.

5. References

- [1] Taherzadeh MJ, Karimi K 2007 *Bioresour Technol.* **2**(3):472–99.
- [2] Dávila I, Robles E, Andrés MA, Gullón P 2017 *Chem Eng Trans.* **57**(2005):85–90.
- [3] Fang C, Schmidt JE, Cybulska I, Brudecki GP, Frankaer CG, Thomsen MH 2015 *Biomed Res Int.* 2015.
- [4] Mittal A, Katahira R, Himmel ME, Johnson DK 2011 *Biotechnol Biofuels*. **4**(1):41.
- [5] Novia, Pareek VK, Agustina TE 2017 MATEC Web of Conf. vol 101 p 1-6
- [6] Salvi DA, Aita GM, Robert D, Bazan V 2010 Appl Biochem Biotechnol. 161(1–8):67–74.

1st International Symposium of Indonesian Chemical Engineering (ISIChem) 2018IOP PublishingIOP Conf. Series: Materials Science and Engineering 543 (2019) 012046doi:10.1088/1757-899X/543/1/012046

- [7] Xin D, Yang Z, Liu F, Xu X, Zhang J 2015 *Bioresour Technol.* **175**:529–36.
- [8] Martínez EL, Quiroga AG, Jardini AL, Filho RM 2009 *Comput Aided Chem Eng.***26**:683–8.
- [9] Carvajal D, Marchisio DL, Bensaid S, Fino D 2012 Ind Eng Chem Res. 51(22):7518–25.
- [10] Pino MS, Rodríguez-Jasso RM, Michelin M, Flores-Gallegos AC, Morales-Rodriguez R, Teixeira JA, Ruiz HA 2018 *Chem Eng J.* 347:119–36.
- [11] Hanra Sebayang A, Haji Hasan M, Hwai Chyuan O, Dharma S, Harjon Bahar A, Susan Silitonga A, Kusumo F 2017 *Chem Eng Trans.* **56**:553–8.
- [12] Datta R 1981 Biotechnol Bioeng. 23(9):2167–70.
- [13] Egan H, Kirk R, Sawyer R 1981*The Luff Schoorl method. Sugars and preserves. In: Pearson's chemical analysis of foods.* 8th ed. Longman Scientific and Technical: Harlow, pp. 152-153.
- [14] ANSYS FLUENT 16.0 Documentation. Canonsburg, Pa, USA.: ANSYS, Inc.; 2015.
- [15] Novia N, Ray S, Pareek V 2007 *Chem Prod Process Model*. **2**(2):4.

Acknowledgments

The authors gratefully acknowledge the financial supports provided by Universitas Sriwijaya for funding the research project through Anggaran DIPA Badan Layanan Umum No. 042.01.2.400953/2018 December 05, 2017 (as Research Contract: Unggulan Kompetitif Universitas Sriwijaya, No. 0007/UN9/SK.LP2M.PT/2018 June 6, 2018).