Water Pollution Evaluation as Consequent Of Old Wells Oil Exploration

by Eddy Ibrahim

Submission date: 10-May-2023 08:46PM (UTC+0700)

Submission ID: 2089471405

File name: 72-204-2-PB_1_water_Polllution.pdf (327.89K)

Word count: 2484 Character count: 12766



Indonesian Journal of Fundamental and Applied Chemistry

Article http://ijfac.unsri.ac.id

Water Pollution Evaluation as Consequent Of Old Wells Oil Exploration (Case study of Angit River village at Babat Toman District of Musi Banyuasin)

Sriyani Sopeana¹, Eddy Ibrahim² and M. Faizal²

¹Student at Environmental Management Graduate Program, Universitas Sriwijaya, Palembang ²Lecture at Environmental Management Graduate Program, Universitas Sriwijaya, Palembang

Email: Sopeana_Iry@yahoo.com

Abstract

This research was aimed to investigate effect of oil spills on surface water from exploration in Dutch well. The investigation was carried out by in situ measurement of some parameters. Water sample was collected by grab sampling method and the analysis was conducted at Laboratory of Environment Badan Lingkungan Hidup dan Penelitian Pengembangan (BLHPP) Kabupaten Musi Banyuasin. The measurement result showed that some parameters did not fulfill the requirement of Standar Quality for Domestic Water Regulation according to Government Regulation No. 82 year 2001 i.e. COD and Oil&Fat content. The surface water and shallow ground water quality had some parameters that did not comply with standar quality according to regulation such as BOD, COD, DO, and oil-fat content. Calculation of pollution indeks (PI) showed that domestic water has 3.26 and was categorized into slightly polluted. At surface water in Angit River, the calculation of PI showed that upstream river was slightly polluted (3.23), while midstream was slightly polluted (3.22) and in downstream river was mildly polluted (9.60).

Keywords: oil exploitation, oil spills, water pollution.

Abstrak

Penelitian ini bertujuan untuk mengkaji pengaruh tumpahan minyak terhadap kualitas air tanah dangkal dan air permukaan Sungai Angit. Penelitian meliputi pengukuran beberapa parameter secara *in-situ*, pengambilan sampel air secara *grab sampling*, analisis sampel air dilakukan di Laboratorium Lingkungan Badan Lingkungan Hidup dan Penelitian Pengembangan (BLHPP) Musi Banyuasin. Hasil dari pengukuran sample air dangkal (sumur penduduk) menunjukkan ada beberapa parameter pengukuran yang tidak memenuhi baku mutu lingkungan (BML) sesuai standar Peraturan Pemerintah RI Nomor 82 Tahun 2001 seperti COD dan kandungan minyak-lemak. Pengukuran sample air permukaan di Sungai Angit menunjukkan ada beberapa parameter pengukuran yang tidak memenuhi baku mutu lingkungan (BML) sesuai standar PP RI Nomor 82 Tahun 2001 yaitu BOD5, COD, DO, dan kandungan minyak-lemak. Hasil dari perhitungan Indeks Pencemaran (IP) sebesar 3.26 menunjukkan bahwa air dangkal tercemar ringan. Indeks Pencemaran di air Sungai Angit menunjukkan bahwa air di hulu mempunyai nilai IP sebesar 3.23 dan air di tengah mempunyai IP sebesar 3,22 yang menunjukkan bahwa air tersebut tercemar ringan. Sedangkan di bagian hilir kegiatan di sungai nilai IP sebesar 9,60 yang menunjukkan bahwa air di hilir kegiatan Sungai Angit tercemar sedang.

Kata Kunci: pertambangan minyak bumi, tumpahan minyak bumi, pencemaran air.

INTRODUCTION

Village of Angit River located at Babat Toman Sub-District, District of Musi Banyuasinis a village with old wells of oil which still has potential petroleum mining. The mining activity can produce approximately 400–500 oil barel per day. Petroleum mining management practiced on old oil well at Angit River is still in traditional manner. The mining is conducted by hand and is assisted by wood

62

DOI: 10.24845/ijfac.v2.i4.62

tripod. Oil spills is inevitable in this mining technique therefore could give deteriorated influence on environment especially water and land quality.

According to regulation provided by ministry of energy and mineral resources, old oil wells is an oil reservoir which had been explored prior 1970 located at non-operated field in the region which no longer under exploration contract by any operator. The oil wells therefore officially are not under legal operation and can be considered as being abandoned.

Oil may caused pollution especially in water due to exploitation and exploration activity which involve refinery process, transportation and piping. Such activities may leak and spills oil into environment and caused water pollution (Nuryantini dan Edi (2010). Old wells oil exploration as a matter of fact increase the living of occupants economically. However, its traditional method and lack of technical standard and environmental safety lead to oil spills which caused water pollution.

Government regulation on toxic and hazardous materials waste management no. 18 year 1999 and no. 85 year 1999 stated that oil spills in the area of oil exploration is categorized as toxic and hazardous materials coded 220. Toxic and hazardous materials defined as materials which endanger both human health and the environment. The materials usually are explosive, easy to burn, chemically reactive, harmful, causing infection, corrosive and carcinogenic.

Here we report the effect of oil spills due to traditional exploration on water resources i.e. surface water and shallow well. The government regulation is used as reference of standard threshold on some parameters measured.

MATERIAL AND METHODS

Materials

Water sample was taken at Village of Angit River located at Babat Toman Sub-District, District of Musi Banyuasin.

Sampling Method

The location of sampling was purposely chosen based on the number of exploration activity conducted in traditional manner.

Samples were taken by means of grab sampling method and were analyzed both in the field and laboratory in accordance with standard procedures. Surface water was taken from Angit River whereas shallow wells water owned by local resident was taken 50 m from exploration site. The Sampling location of Angit River is displayed on Table 1.

Table 1. Sampling location of Angit River.

Station	Coordinate	Position		
A.1	S 02°39'23,2"	Up stream of exploration		
	E 103°34'44,5"	location of off old wells		
A.2	S 02°39'22,0"	Mid stream of exploration		
	E 103°34'48,8"	location of oil old wells		
A.3	S 02°39'38,5"	Down stream of exploration		
	E 103°34'34,5"	location of oil old wells		
A.4	S 02°39'22,8"	Waste water of oil old wells		
21.7	E 103°34'44,7"	exploration		
A.5	S 02°39'30,0"	Wells owned by local resident		
	E 103°34'48,0"	distance 20 m (Shallow wells water)		

Analysis Data

Water samples were treated and analyzed by using appropriate method to obtain parameters value needed on investigation process. The method and parameters to be determined is displayed on Table 2.

Tabel 2. Result of parameters measurement of waste water from exploration activity.

Parameter	Max. value allowed	Method	
COD	300 mg/l	SNI 06-6989.2-2004	
Oil and fat	25 mg/l	SNI 06.6989.10-2004	
NH_3N	10 mg/l	SNI 06.6989.30-2005	
Temperature	45°	SNI 06-6989.23-2005	
pН	6 - 9	SNI 06-6989.11-2004	
TDS	4000 mg/l	SNI 06.6989.27-2005	

Ref.: Provisioned by ministry of environmental no 19 year 2010

Water samples taken from surface and shallow wells were also treated and analyzed using similar method. The result is showed on Table 3.

Tabel 3. Result of parameters measurement of surface water and shallow wells water.

Parameter	Unit	Water class		
		Class I	Class III	
Physical				
Temperature	°C	Native ± 3	Native ± 3	
TDS	mg/l	1000	1000	
TSS	mg/L	50	400	
Chemical/Inor	rganic			
pH	-	6 - 9	6 - 9	
BOD	mg/L	2	6	
COD	mg/L	10	50	
DO	mg/l	6	3	
NH_3N	mg/l	0,5	-	
Chemical organic				
Oil and fat	μg/L	1000	1000	

Source: PP No 82 2001 Tentang Pengelolaan Kualitas Air dan Pengendalian Pencemaran Air

Data Analysis

Analysis was conducted to define water quality status which indicate water quality level from particular source compare to standard threshold approved. One of method of defining water quality status is using pollution index. Pollution index is adapted by ministry of environmental provision no 115 year 2003 on guideline of water quality status determination.

Pollution index (PI_j) was calculated using the following formula:

$$PI_{j} = \sqrt{\frac{\left(\frac{C_{i}}{L_{ij}}\right)_{M}^{2} + \left(\frac{C_{i}}{L_{ij}}\right)_{R}^{2}}{2}} \tag{1}$$

Whereas:

C_i = laboratory analysis result

R = average value

 L_{ij} = standard threshold value

M = maximum value

Based on the pollution index, the water quality status is classified accordingly. The classification of water quality status is as follow displayed on Table 4.

Table 4. Water quality status according to pollution index

Pollution index	Water quality status
0≤ PI ≤1.0	Good
$1.0 < PI \le 5.0$	Slightly polluted
$5.0 < PI \le 10$	Mildly polluted
PI> 10	Heavily polluted

Ref.: Ministry of environmental provision no. 115 year 2003.

RESULT AND DISCUSSION

The acidity of waste water from old wells oil exploration was determined by measuring pH. The pH obtained is 5.71 which indicate waste water is not fulfill the requirement of environmental threshold quality between 6–9 (Ministry provision no. 19 year 2010). Sample analysis result of waste water from old wells oil exploration displayed on Table 5.

Table 5. Sample analysis result of waste water from old wells oil exploration

wens on exploration					
Parameter	unit	result	Standard	Status	
			treshold*		
COD	mg/l	97	300	comply	
Oil & fat	mg/l	< 5	25 mg/l	Comply	
NH_3N	mg/l	3	10	Comply	
Temperature	°C	31	45	Comply	
pH	#	5,71	6-9	Not	
				comply	
TDS	mg/l	3,32	4000	Comply	

Sample from shallow ground water resource was tested against several parameters. Result showed COD and oil and fat did not comply standard threshold approved by Government regulation no 82 year 2001. COD result 11 mg/L while oil and fat 10 mg/L exceed maximum value allowed by regulation.

Table 6. Analysis result of water from local resident well.

Parameter	unit	result	Standard threshol*	Status
			class I	
Temperatur	°C	30	native± 3	comply
TDS	mg/l	98	1000	Comply
TSS	mg/l	37	50	Comply
pH	#	6.24	6-9	Comply
BOD_5	mg/l	1.8	2	Not
				Comply
COD	mg/l	11	10	Not
				Comply
DO	mg/l	2.82	6	Not
				Comply
NH_3N	mg/l	0.2	0.5	Comply
Oil and fat	mg/l	< 5	1	Not
				Comply

Table 6 displayed some parameters did not comply the required value provisioned by the Government regulation no 82 year 2001. The parameters which did not comply are BOD₅, COD, DO and oil and fat.

The result on Table 6 also confirmed that water from Angit river has the highest concentration of BOD5, COD, DO and oil and fat at downstream. This fact can be seen as result of accumulation process of oil spills from exploration activity of old oil wells. The exploration activity is located near by the river therefore water was polluted inevitably.

The highest BOD₅ value according to laboratory testing is 1535 mg/L which is far above value allowed at 6 mg/L. COD value has highest value at 7872 mg/L while threshold approved is 50 mg/L and DO was obtained at 3.91 mg/L whereas threshold approved is 3 mg/L. The oil and fat parameter showed similar tendency given the analysis result at 10 mg/L where as standard threshold allow only 1 mg/L. Table 8 provide Analysis result of water from Angit River.

Table 7. Analysis result of water from Angit river

Parameter	Up	Mid	Down	Standard
Parameter	stream	stream	stream	Standard
Temperature	30	31	30	native ± 3
TDS	87.1	36.2	26.8	1000
TSS	48	45	66.0	400
pН	6.53	6.12	6.40	6-9
BOD_5	2	1.65	1535	6
COD	15	9	7872	50
DO	3.62	1.32	3.91	3
NH_3N	0.2	0.2	0.40	(-)
Oil and fat	< 5	< 5	10	1

Article http://ijfac.unsri.ac.id

Pollution index calculated for Angit River can be concluded as slightly to mildly polluted. Table 8 provide result of calculation and the status resolved.

Table 8. Pollution index calculation result of Angit river

Location	PI value	Pollution status
Shallow water	3.26	Slightly polluted
(Local resident well)		
River water	3.23	Slightly polluted
(Upstream)		
River water	3.22	Slightly polluted
(Midstream)		
River water	9.60	Mildly polluted
(Downstream)		

CONCLUSION

The old wells oil exploration at Angit river village caused water pollution due to oil spills. Among the water parameters tested, BOD₅, COD, DO and oil and fat did not comply to required value approved by regulation. Pollution index calculation conclude that water used by local resident at Angit river village is slightly to mildly polluted.

REFERENCES

- A. Sitanala, Konservasi Tanah dan Air. IPB Press, Bogor, 2009.
- [2] R. M. Atlas and C. E. Cerniglia, "Bioremediation of Petroleum Pollutants," *Bioscience*, vol. 45, no. 5, pp. 332–338, May 1995.
- [3] F. Aguilera, J. Méndez, E. Pásaro, and B. Laffon, "Review on the effects of exposure to spilled oils on human health," *J. Appl. Toxicol.*, vol. 30, no. 4, pp. 291–301, May 2010.
- [4] N. C. Brady and R. R. Weil, *The nature and properties of soils*, 14th ed. Pearson, 2013.
- [5] L. C. M. Santos, M. Cunha-Lignon, Y. Schaeffer-Novelli, and G. Cintrón-Molero, "Long-term effects of oil pollution in mangrove forests (Baixada Santista, Southeast Brazil) detected using a GIS-based multitemporal analysis of aerial photographs," *Brazilian J. Oceanogr.*, vol. 60, no. 2, pp. 159–170, Jun. 2012.
- [6] L. C. M. Santos, M. Cunha-Lignon, Y. Schaeffer-Novelli, and G. Cintrón-Molero, "Long-term effects of oil pollution in mangrove forests (Baixada Santista, Southeast Brazil) detected using a GIS-based multitemporal analysis of aerial photographs," Brazilian J. Oceanogr., vol. 60, no. 2, pp. 159–170, Jun. 2012.
- [7] C. Charlena, Z. A. Mas'ud, A. Syahreza, and A. S. Purwadayu, "Profil kelarutan limbah minyak bumi alam air akibat pengaruh surfaktan nonionik dan laju pengadukan," *Chem. Progr.*, vol. 2, no. 2, pp. 69–78, 2009.

- [8] D. Ibarra-Mojica, A. Romero, C. Barajas-Ferreira, V. Kafarov, and C. Barajas-Solano, "Methodological proposal for evaluation of oil spills environmental vulnerability in rivers," in *International oil spill proceedings*, 2017, pp. 1806–1818.
- [9] M. Fingas, The basics of oil spill cleanup, Third. Boca Raton: CRC Press, 2012.
- [10] Keputusan Menteri Lingkungan Hidup Nomor 115 Tahun 2003. Pedoman Penentuan Status Mutu Air
- [11] Nuryatini and E. I. Wiloso, "Uji metode analisis minyak terdispersi dalam air," *Teknol. Indones.*, vol. 33, no. 1, Nov. 2012.
- [12] M. J. Plebon, "TORR The Next Generation of Hydrocarbon Extraction From Water," J. Can. Pet. Technol., vol. 43, no. 9, pp. 15–18, Sep. 2004.
- [13] R. C. Prince, R. R. Lessard, and J. R. Clark, "Bioremediation of Marine Oil Spills," *Oil Gas Sci. Technol. – Rev. IFP*, vol. 58, no. 4, pp. 463–468, 2003.
- [14] Peraturan Menteri Negara Lingkungan Hidup No 19 Tahun 2010. Baku Mutu Limbah Bagi Usaha dan/atau Kegiatan Minyak dan Gaserta Panas Bumi
- [15] Peraturan Pemerintah Nomor 82 Tahun 2001. Pengelolaan Kualitas Air dan Pengendalian Pencemaran Air.
- [16] S. Sulistyono, S. Suntoro, and M. Masykuri, "Kajian dampak tumpahan minyak dari kegiatan operasi kilang minyak terhadap kualitas air dan tanah (Studi Kasus Kilang Minyak Pusdiklat Migas Cepu)," Ekosains, vol. 4, no. 2, pp. 23–34, Jul. 2011.
- [17] J. Tang, N. Xiaowei, S. Qing, R. Wang. Bioremediation of Petroleum Polluted Soil by Combination of Ryegrass with Effective Microorganisms. J. Enviro. Technol. Eng., vol. 3, no. 2, pp. 80–86, 2010.
- [18] W. Widowati, A. Sastiono, R. Jusuf, *Efek Toksik Logam Pencemaran dan Penanggulangan Pencemaran*. CV. Andi Offset. Yogyakarta, 2008.
- [19] W. Viessman and W. Viessman, Water supply and pollution control. Pearson Prentice Hall, 2009.

DOI: 10.24845/ijfac.v2.i4.62

Water Pollution Evaluation as Consequent Of Old Wells Oil Exploration

ORIGINALITY REPORT

17% SIMILARITY INDEX

13%
INTERNET SOURCES

12% PUBLICATIONS

6% STUDENT PAPERS

MATCH ALL SOURCES (ONLY SELECTED SOURCE PRINTED)

1%

★ Rezky Dwi Satria Isna Apriani Kiki Priyo Utomo. "ANALISIS KANDUNGAN TIMBAL (Pb) DAN KADMIUM (Cd) DI TPA RASAU JAYA KABUPATEN KUBU RAYA", Jurnal Teknologi Lingkungan Lahan Basah, 2015

Publication

Exclude quotes

Exclude bibliography

Off

Exclude matches

Off