

# Analysis of the Emission Reduction through Performance Improvement of Intersection and Network nearby Using Micro Simulation Program

*By* Joni Arliansyah



## RESEARCH ARTICLE 3

## Analysis of the Emission Reduction through Performance Improvement of Intersection and Network nearby Using Micro Simulation Program

Joni Arliansyah\* and Ragil Tri Bawono

Department of Civil Engineering, Faculty of Engineering, University of Sriwijaya, Jl. Raya Palembang-Prabumulih KM 32, Inderalaya, 30602, Indonesia

11

Received: August 30, 2018

Revised: September 30, 2018

Accepted: October 3, 2018

**Abstract:****Introduction:**

Palembang as one of the big cities in Indonesia is the capital city of South Sumatra Province. Congestion occurs at the main intersections of the city, one of which is Simpang Patal Pusri which has a long queue and delays in peak hour of 655 m and 490 seconds. The action performed to improve traffic performance and reduce the air pollution at this intersection was the underpass construction. This study discussed the importance of constructing an underpass together with improving geometric design and traffic management at the nearest intersections to obtain optimal results in addressing traffic problems and emissions reductions.

**Methods:**

To analyze the performance of traffic intersection and its network, Vissim simulation micro program and Program Moves were used to find out the emission values of Total Carbon, NOx and PM10 of the analyzed handling scenarios.

**Results:**

The results showed that the construction of an underpass accompanied by the improved geometric design and traffic management at the nearest intersection produced better intersection performance and emission reductions when compared to only underpass construction, where the average V/C decreased from 0.87 to 0.77, the average queue decreased from 290.3 m to 190.57 m, and the average delay decreased from 106.34 seconds to 85.07 seconds. The values of Total Carbon, NOx and PM10 also decreased significantly on all the roads in the study area.

**Conclusion:**

Based on the analysis, a scenario of the underpass construction is combined with geometric improvement and traffic management at the intersections which provides the best traffic performance and emissions reduction at either the intersections or road segments of the road network being studied.

**Keywords:** Congestion, Underpass, Traffic Management, Traffic Performance, Emission Decrease, Micro simulation program.

### 1. INTRODUCTION

Palembang city with the number of population of 1.8 million people is the activity center of South Sumatra Province. The level of the existing vehicle movement in the city causes traffic congestion at city road networks and accumulation of vehicle exhaust emissions.

Palembang is a big city and construction of a flyover or underpass at a major intersection is necessary in order to

\* Address Correspondence to this author at the Department of Civil Engineering, Faculty of Engineering, University of Sriwijaya, Jl. Raya Palembang-Prabumulih KM 32, Inderalaya, 30602, Indonesia; Tel: 0711-580139; E-mail: [joniarliansyah@yahoo.com](mailto:joniarliansyah@yahoo.com)

overcome the traffic congestion and diminish the vehicle exhaust emissions at the intersection. In addition, Arliansyah *et al.* [1] state that a problem of network performance can be improved with the development of road network and bridges crossing Musi River that divides Palembang City. At the macro level, road network development should also be accompanied by traffic arrangement of the intersection. In 2014, the underpass was constructed at Patal Pusri intersection to overcome the congestion problems where the queue length and delay reached 655 m and 490 s.

Gastaldi *et al.* [2] point out that an intersection is a critical part of a road network because its performance affects the air quality in which a control type and an intersection geometric configuration can provide a significant effect on vehicle emission. The congestion on the intersection will decrease the air quality produced by vehicle emission. Lin *et al.* [3] conducted a study on optimizing intersections by algorithm that optimized PI (the comprehensive benefit value) and V/C for an Isolated Signalized Intersection to obtain the decreased emission and optimal delay. Chandan *et al.* [4] developed an algorithm for optimizing traffic lights connected to vehicles at isolated intersections which were then tested with the VISSIM program. However, if the intersection has reached its saturation condition, separating the main flow of traffic at the intersection by constructing an underpass or flyover is the best way.

Because of the emission reduction, the performance of an intersection and its road network nearby were affected by the performance of the nearest intersection which needed reviewing geometric design and performing a traffic management at the intersection and roads near the Underpass of Patal Pusri. This study analyzed the importance of constructing an underpass accompanied by geometric improvement and traffic management at nearby intersections and road networks to obtain optimal results in addressing traffic problems and emissions reductions.

## 2. PROGRAM OF TRAFFIC MICROSIMULATION AND EMISSION CALCULATION

Software of micro-simulation traffic is a program used to represent traffic conditions from real conditions that run like a simulated traffic situation. The simulation is carried out by embodying the driver behavior on the road and the road network enabling to measure the impact of travel patterns and changes that occur in the study area. This program has the ability to calculate delays, queue lengths, free flow speed, and service levels on both road and road networks. With this ability, the program is suitable for the use of analyzing traffic conditions in urban and suburban areas including analyzing from the types of intersections to the analysis of a study area. The micro-simulation program can show the impact of an environmental change occurring in the study area such as bottle neck, road geometry change, traffic flow diversion, or traffic light optimization. The analysis conducted on the micro-simulation program can be done either statically or dynamically. Dynamic analysis enables the simulation programs to accommodate the dynamics of traffic conditions at the site. Some studies on analyzing traffic performance using traffic micro-simulation programs have been reported [5 - 10].

MOVES is a calculation program to estimate the emission production in some area that simulated every second. The estimation is influenced by driving behaviour, delay, duration and vehicle characteristic measured by using VSP (Vehicle Specific Power) or STP (Scaled Tractive Power) method. The integration of traffic micro-simulation models and emission models have been reported [11 - 14]. Monitoring system of city carbon emission was carried out by Sun *et al.* [15] utilizing various kinds of equipment to gather the data of traffic flow, meteorological conditions, vehicular carbon emissions and driving characteristics on a typical road. The emission model Moves was used to analyze the traffic carbon emission. In addition, emission calculation using computer programs such as COPERT and ENVIVER were reported [16, 17].

## 3. METHODOLOGY

Fig. (1) shows the study location where the Patal Pusri intersection is adjacent to 2 intersections of Seduduk Putih and Taman Kenten.

The procedure method of the study is described as follows:

1. Data collection of traffic flow, free flow speed and geometric condition of the network.
2. Modeling of the existing traffic condition at Patal Pusri intersection and the two nearby intersections using simulation micro program of VISSIM.
3. Calibration of the model.
4. The development of traffic condition handling scenario is as follows:
  1. Existing traffic condition of the network without doing anything (Scenario 1).
  2. Constructing the underpass at Patal Pusri intersection without being combined with the traffic

- management at the nearest intersection (Scenario 2).
3. Analyzing of intersection performance of Patal Pusri network with geometric change and traffic management at intersections near Underpass Patal-Pusri intersection (Scenario 3). Layout of Underpass Patal-Pusri, geometric change at Seduduk Putih intersection and Taman Kenten intersection are shown in Figs. (2, 3 and 4) consecutively. There is a 3.5 meter wide additional road with the length of 70 meters to avoid queue length and delay at peak hour. Traffic management mentioned in scenario 3 means diverting the vehicle exit from Seduduk Putih intersection to another road shown in Fig. (5).
  5. Evaluation of network performance and emission reduction was conducted for each developed scenario. Evaluation of network performance used queue length and delay while the emission parameters were total carbon, NOx and PM10. Moves Program was used to calculate the emission.



**Fig. (1).** Study location.



**Fig. (2).** Underpass construction at Patal-Pusri intersection.




Fig. (3). Geometric improvement at Taman Kenten intersection.




Fig. (4). Geometric improvement at Seduduk Putih intersection.





Fig. (5). Traffic Management at Seduduk Putih Intersection.

#### 4. RESULT

##### 4.1. Calibration of Model

In the VISSIM program, the calibration process was carried out by changing the minimum headway distance parameters, where the default value of minimum headway distance parameters in the VISSIM program was 0.5 m. The calibration process was conducted by changing the minimum value of headway distance with the following scheme:

- Minimum headway distance = 0.7 m.
- Minimum headway distance = 1.3 m.

Traffic volume data and free flow speed were used for the developed model calibration by comparing the traffic volume and free flow speed of modeling result with field value. It is very important to obtain a good result of calibration and validation of the micro-simulation model in order to have a reliable estimation of the emission produced by the vehicles. Table 1 shows the calibration criteria used in this study.

Table 2 and Fig. (6) show the comparison between the number of the modeled vehicles and the number of the observed vehicles starting from 4 p.m. to 6 p.m. representing the peak hours at Seduduk Putih intersection to MP Mangkunegara Street. Table 2 indicates that the optimum minimum headway distance value is optimally 0.7 with 92% similarity value. The value of similarity with default setting of minimum headway distance of 0.5 resulted in average model resemblance of 70%, while the minimal headway distance of 1.5 m only produced average model resemblance of 58%. It is obvious that the modeling volume approached the field volume and had values that met the calibration criteria shown in Table 1.




Fig. (6). Modeled vehicle vs. observed vehicle.

Table 1. Calibration criteria.

No	Criteria and Measurement	Calibration Accepted Target
1	Modeled number of vehicle hourly flow vs. observed number of vehicle flow	85%
2	Modeled speed vs. observed speed	85%

Table 2. Number of vehicle from Seduduk Putih street to MP Mangkunegara street.

Time	Observed	Modeled	Similarity (%)
16.00 - 16.15	35	32	91%
16.15 - 16.30	50	52	104%
16.30 - 16.45	39	36	92%
16.45 - 17.00	56	48	86%
17.00 - 17.15	59	54	92%
17.15 - 17.30	45	41	91%
17.30 - 17.45	57	49	86%
17.45 - 18.00	43	42	98%
Average similarity			92%

Table 3 and Fig. (7) show that the calibration of free flow speed also indicates that the model reached 96% of the average similarity. The average similarity means that the created model represented 96% similarity of free flow speed at the real condition.




Fig. (7). Modeled free flow speed vs. observed free flow speed.

The calibration result shown in Tables 2 and 3 indicate that the model has already reflected the real condition which means the simulation model is ready for use in the analyses.

Table 3. Modeled free flow speed vs. observed free flow speed.

Location	Modeled Speed (Km/H)	Observed Speed (Km/H)	Similarity
Underpass	52	55	95%
Seduduk Putih	33	36	92%
Taman Kenten	32	31	103%
Average			96%

#### 4.2. Network Performance


Evaluation of network performance was conducted for the three developed scenarios. Table 4 shows the Volume per Capacity ratio (V/C), delay and the queue length of all intersections of each developed scenario.

Table 4 illustrates that the existing condition of Simpang Patal Pusri was overloaded and saturated by the traffic. Compared with the second scenario, the V/C ratio decreased less than the first one but the amount was still near the full capacity indicating that the second scenario did not give an impactful result. While the third scenario shows the lowest V/C ratio, where it decreased 56% compared to the existing condition. It was the same as those of Taman Kenten Intersection and Seduduk Putih Intersection where the V/C ratio decreased as much as 68% at both intersections.

**Table 4.** V/C ratio, delay and queue length for each scenario.

No	Condition	Intersection	V/C	Maximum Queue Length (m)	Delay (s)
1	Existing (Scenario 1)	Patal Pusri	1.40	797.00	498.00
		Taman Kenten	1.10	504.72	135.77
		Seduduk Putih	1.16	211.18	184.68
2	Underpass (Scenario 2)	Patal Pusri	0.96	423.00	120.00
		Taman Kenten	0.83	256.08	89.02
		Seduduk Putih	0.82	191.68	130.00
3	Underpass + Traffic Management (Scenario 3)	Patal Pusri	0.81	200.00	84.00
		Taman Kenten	0.75	78.21	76.15
		Seduduk Putih	0.74	26.75	76.4

Based on Table 4 the existing condition of Patal Pusri intersection had a long queue of 797 meters and a delay of 498 seconds. The second scenario shows when an underpass was built, it would reduce the queue length and delay. The third scenario shows the best result that reduced maximum queue length for 33% and decreased the delay until 42% compared to the existing condition. Fig 8 (shows that the underpass construction combined with geometric improvements and traffic management at the nearest intersection could improve the performance of the studied roads on the road network. It is clear that constructing an underpass combined with management route of traffic at the intersection close to the underpass is the best scenario for having the best network service.



**Fig. (8).** Performance of road network after the application of scenario 3.

**4.3. Integration VISSIM to MOVES Program**

The emission was estimated using MOVES (Motor Vehicle Movement) by which a weighted average of emission was calculated using an operating mode. The exhaust emission was operated using VSP (Vehicle Specific Power) or STP (Scaled Tractive Power). Both VSP and STP were calculated based on a vehicle’s speed and acceleration, but they were different in how they were scaled. The formula of VSP and STP is given in equations (1) and (2) as follows:

$$VSP = \frac{Av}{M} + \frac{Bv^2}{M} + \frac{Cv^3}{M} + (a + g \sin \theta)v \tag{1}$$



$$STP = \frac{Av + Bu^2 + Cv^3 + Mva}{f} \tag{2}$$

where VSP is the Vehicle Specific Power (kw/ton), STP the Scaled Tractive Power (kw/ton), M is mass of each vehicle (metric tons), A is term of rolling (kw-s/m), B is term of rotating (kw-s<sup>2</sup>/m<sup>2</sup>), C is term of the aerodynamic (kw-s<sup>3</sup>/m<sup>3</sup>), v is the fix vehicle speed (m/s), a is the dynamic of acceleration (m/s<sup>2</sup>), g is the gravity force (m/s<sup>2</sup>), θ is the road grade angle, and f is the mass factor for vehicle.

Hatem *et al.* [18] analyzed emissions on road segments resulted from the vehicle traffic using the VISSIM program that was integrated with the MOVES program with an analysis of every second of the rush hour condition. They found out that the vehicle emission calculations derived from the integration of Vissim and Moves programs provided better results. Xiaodan *et al.* [19] state that estimating transport network emissions in Monte Carlo used a Vissim program integrated with MOVES.

**4.4. Result of Vehicle Emission Calculation**

Tables 5 and Table 6 show the results of comparison of CO, NOx and PM10 using Moves program for the three analyzed scenarios. It shows that the three types of emission decreased in Scenario 2 (Sc2) and Scenario 3 (Sc3). Analyses of variance for the data in Table 6 yields F value as shown in Table 7 while Table 8 shows the P value comparison among scenarios.

**Table 5. Moves results of emission calculation.**

Source type	Link number	Total Carbon Emissions (kg/hr)			NOx Emissions (kg/hr)			PM10 Emissions (kg/hr)		
		Sc1	Sc2	Sc3	Sc1	Sc2	Sc3	Sc1	Sc2	Sc3
Motorbike	1	2.3680	1.9013	1.3013	0.2133	0.2633	0.1067	0.0021	0.0032	0.0012
	2	4.0380	3.4980	2.7680	0.4367	0.4633	0.2933	0.0043	0.0051	0.0023
	3	4.0880	3.4247	2.6713	0.4200	0.4667	0.2733	0.0041	0.0056	0.0024
	4	3.0480	3.2213	2.5147	0.4333	0.3600	0.2733	0.0043	0.0029	0.0019
	5	2.5380	2.9047	2.2780	0.4000	0.3033	0.2533	0.0039	0.0020	0.0017
	6	2.8747	2.9713	2.2947	0.3767	0.3467	0.2467	0.0037	0.0027	0.0018
	7	3.0080	3.0047	2.2480	0.3733	0.3667	0.2300	0.0037	0.0031	0.0019
	8	3.0480	3.0247	2.2647	0.3700	0.3633	0.2300	0.0036	0.0032	0.0019
Total (Motorbike)		25.01	25.0107	23.9507	18.3407	3.0233	2.9333	1.9067	0.0277	0.0151
Cars	1	2.1860	1.7793	1.3860	0.3203	0.2037	0.1770	0.0040	0.0002	0.0014
	2	3.8627	2.8960	2.4493	0.4803	0.3770	0.2837	0.0069	0.0041	0.0043
	3	3.9927	2.6627	2.5227	0.4870	0.3670	0.2837	0.0070	0.0050	0.0041
	4	2.9460	2.4293	2.3360	0.3803	0.3737	0.2937	0.0041	0.0051	0.0032
	5	2.2793	2.2193	2.1427	0.3270	0.3837	0.2870	0.0030	0.0047	0.0028
	6	2.5193	2.1993	2.1293	0.3670	0.3003	0.2737	0.0038	0.0047	0.0027
	7	3.0060	2.6627	2.1660	0.3870	0.3303	0.2603	0.0045	0.0043	0.0030
	8	2.9127	2.4560	2.2027	0.3870	0.2937	0.2603	0.0044	0.0043	0.0031
Total (Cars)		23.70	23.7047	19.3047	17.3347	3.1360	2.6293	2.1193	0.0325	0.0245
Bus	1	0.1000	0.1067	0.0733	0.3600	0.3500	0.2300	0.0278	0.0270	0.0176
	2	0.1833	0.1700	0.1600	0.6967	0.5500	0.4700	0.0496	0.0392	0.0335
	3	0.1833	0.1767	0.1500	0.6767	0.5733	0.4633	0.0477	0.0407	0.0321
	4	0.1500	0.1333	0.1367	0.5833	0.4167	0.4367	0.0377	0.0310	0.0295
	5	0.1300	0.1133	0.1200	0.5133	0.3567	0.3967	0.0331	0.0267	0.0271
	6	0.1500	0.1333	0.1233	0.5967	0.4267	0.3933	0.0427	0.0305	0.0277
	7	0.1567	0.1367	0.1233	0.5967	0.4433	0.3933	0.0414	0.0310	0.0272
	8	0.1600	0.1500	0.1267	0.5967	0.4967	0.4000	0.0421	0.0356	0.0273
Total (Bus)		1.21	1.2133	1.1200	1.0133	4.6200	3.6133	3.1833	0.2618	0.2220

(Table 5) contd....

Source type	Link number	Total Carbon Emissions (kg/hr)			NOx Emissions (kg/hr)			PM10 Emissions (kg/hr)		
		Sc1	Sc2	Sc3	Sc1	Sc2	Sc3	Sc1	Sc2	Sc3
Trucks	1	0.1253	0.1320	0.0987	0.3737	0.3637	0.2437	0.0344	0.0337	0.0237
	2	0.2087	0.1953	0.1853	0.7103	0.5637	0.4837	0.0555	0.0456	0.0397
	3	0.2087	0.2020	0.1753	0.6903	0.5870	0.4770	0.0543	0.0469	0.0384
	4	0.1753	0.1587	0.1620	0.5970	0.4303	0.4503	0.0446	0.0371	0.0358
	5	0.1553	0.1387	0.1453	0.5270	0.3703	0.4103	0.0397	0.0333	0.0335
	6	0.1753	0.1587	0.1487	0.6103	0.4403	0.4070	0.0492	0.0376	0.0335
	7	0.1820	0.1620	0.1549	0.6103	0.4570	0.4070	0.0492	0.0378	0.0333
	8	0.1853	0.1753	0.1520	0.6103	0.5103	0.4137	0.0493	0.0412	0.0334
Total (Truck)		1.4160	1.4160	1.3227	1.2223	4.7293	3.7227	3.2927	0.3131	0.2713
Total Emissions		51.3447	45.6980	37.9109	15.5087	12.8987	10.5020	0.7655	0.6352	0.5330

Table 6. Generated total emissions.

Link Number	Total Carbon (kg/hr)			NOx (kg/hr)			PM 10 (kg/hr)		
	Sc1	Sc2	Sc3	Sc1	Sc2	Sc3	Sc1	Sc2	Sc3
1	4.7793	3.9193	2.8593	1.2673	1.1807	0.7573	0.0683	0.0641	0.0438
2	8.2927	6.7593	5.5627	2.3240	1.9540	1.5307	0.1163	0.0940	0.0797
3	8.4727	6.4660	5.5193	2.2740	1.9940	1.4973	0.1131	0.0982	0.0770
4	6.3193	5.9427	5.1493	1.9940	1.5807	1.4540	0.0907	0.0762	0.0704
5	5.1027	5.3760	4.6860	1.7673	1.4140	1.3473	0.0796	0.0666	0.0651
6	5.7193	5.4627	4.6960	1.9507	1.5140	1.3207	0.0994	0.0755	0.0657
7	6.3527	5.9660	4.6923	1.9673	1.5973	1.2907	0.0987	0.0762	0.0653
8	5.0843	5.3345	4.7460	1.7246	1.6640	1.3040	0.0743	0.0694	0.0658

Table 7. Statistic F Value of ANOVA (Analysis of Variance).

Emission Gas	F Value	Sig
Total Carbon	4.042	0.033
NOx	8.788	0.002
PM 10	7.033	0.005

Table 8. P Value of multiple comparison between scenarios.

Scenario	Sc 1	Sc 2	Sc 3
Sc 1		0.537 <sup>a</sup>	0.034 <sup>a</sup>
		0.139 <sup>b</sup>	0.002 <sup>b</sup>
		0.121 <sup>c</sup>	0.005 <sup>c</sup>
Sc 2	0.537 <sup>a</sup>		0.261 <sup>a</sup>
	0.139 <sup>b</sup>		0.133 <sup>b</sup>
	0.121 <sup>c</sup>		0.311 <sup>c</sup>
Sc 3	0.034 <sup>a</sup>	0.034 <sup>a</sup>	
	0.002 <sup>b</sup>	0.002 <sup>b</sup>	
	0.005 <sup>c</sup>	0.005 <sup>c</sup>	

Note: <sup>a</sup> is P Value of Total Carbon; <sup>b</sup> is P Value of NOx; <sup>c</sup> is P Value of PM10

Table 7 shows that there are significant differences of each emission gas among the scenarios while Table 8 shows the significant differences among the scenarios. It is apparent that each scenario gives a decreasing effect of vehicle emission reduction in the road network of the studied location. Table 8 shows that the scenario of the underpass construction combined with the geometric improvement and traffic management at nearby intersection (Sc 3) produced the best result of emission reduction compared to the other scenarios, meaning that compared with the existing condition this scenario can significantly decrease the air pollution. Consequently, it is important to improve the performance of nearby intersection when conducting an action of improving a performance of the main intersection.

Fig. (9) shows the cumulative emission of each road segment of the studied areas. It is obvious that the emission reduction occurred in all road segments being studied at Scenarios 2 and 3. Links 5 (Seduduk Putih Street) and 8 (Taman Kenten Street) produced the least emission compared to other links.




Fig. (9). Emissions on roads in the study area.

**CONCLUSION**

This study discusses the importance of constructing an underpass accompanied by geometric improvements and traffic management at the nearest intersection and road network to obtain optimal results in addressing traffic problems and emissions reductions.

If compared to only constructing the underpass, a scenario of the underpass construction is combined with geometric improvement and traffic management at the nearest intersections to provide the best traffic service performance result at both the intersections and road segments of the road network.

The underpass construction combined with the geometric improvement and traffic management at the nearest intersections could also significantly reduce air pollution at all road segments of the studied areas.

In general, the study shows that to obtain the best traffic service and emission reduction at both intersections and road segments of the road network, the handling of problematic main intersections needs to go along with the management of traffic and geometric improvement at the intersections nearby.

2

**CONSENT FOR PUBLICATION**

Not applicable.

## CONFLICT OF INTEREST

The authors declare no conflict of interest, financial or otherwise.

## ACKNOWLEDGEMENTS

Declared none.

## REFERENCES

- [1] J. Arliansyah, M.R. Prasetyo, and A.Y. Kurnia, "Planning of city transportation infrastructure based on macro simulation model", *Int. J. Adv. Sci. Eng. Inf. Technol.*, vol. 7, no. 4, pp. 1262-1267, 2017. [Online] Available: <http://dx.doi.org/10.18517/ijaseit.7.4.2444>
- [2] M. Gastaldi, C. Meneguzzo, R. Rossi, L.D. Lucia, and G. Gecchele, "Evaluation of air pollution impacts of a signal control to roundabout conversion using micro-simulation, 17th Meeting of the EURO Working Group on Transportation Spain", *Transp. Res. Procedia*, vol. 3, pp. 1031-1040, 2014. [<http://dx.doi.org/10.1016/j.trpro.2014.10.083>]
- [3] C. Lin, B. Gong, and X. Qu, "Low emissions and delay optimization for an isolated signalized intersection based on vehicular trajectories", *PLoS One*, vol. 10, no. 12, p. e0146018, 2015. [<http://dx.doi.org/10.1371/journal.pone.0146018>] [PMID: 26720095]
- [4] K. Chandan, A. M. Seco, and A. B. Silva, "Real-time Traffic Signal Control for Isolated Intersection, using Car-following Logic under Connected Vehicle Environment", *World Conference on Transport Research WCTR Shanghai*, pp. 1610-1625, 2016.
- [5] R.H. Della, J. Hanafiah, Arliansyah, and R. Artiansyah, "Traffic performance analysis of u-turn and fly over u-turn scenario; a case study at Soekarno Hatta Road, Palembang, Indonesia, The 5th International Conference of Euro Asia Civil Engineering Forum (EACEF-5)", *Procedia Eng.* 125, pp. 461-466, 2015. [<http://dx.doi.org/10.1016/j.proeng.2015.11.123>]
- [6] J. Arliansyah, and R.T. Bawono, "Study on Performance of Intersection Around The Underpass Using Micro Simulation Program, IOP Conf. Ser.: Earth Environ. ", *Sci.* 124, 2018
- [7] D. Lin, X. Yang, and C. Gao, "VISSIM-based Simulation Analysis on Road Network of CBD in Beijing", 13th COTA International Conference of Transportation Professionals", *Procedia Soc. Behav. Sci.*, vol. 96, pp. 461-472, 2013. [<http://dx.doi.org/10.1016/j.sbspro.2013.08.054>]
- [8] H. T. Abdelwahab, "Traffic micro-simulation model for design and operational analysis of barrier toll stations", *Ain Shams Eng. J.*, vol. 8, pp. 507-513, 2016. [Online] Available: <https://doi.org/10.1016/j.asej.2016.05.010> [Accessed Des. 30, 2017]
- [9] D. Salgado, D. Jolovic, P.T. Martin, and R.M. Aldrete, "Traffic Micro-simulation Models Assessment – A Case Study of International Land Port of Entry, The 7th International Conference on Ambient Systems, Networks and Technologies (ANT 2016)", *Procedia Comput. Sci.*, vol. 83, pp. 441-448, 2016. [<http://dx.doi.org/10.1016/j.procs.2016.04.207>]
- [10] D.J. Sun, L. Zhang, and F. Chen, "Comparative study on simulation performances of CORSIM and VISSIM for urban street network", *Simul. Model. Pract. Theory*, vol. 37, pp. 18-29, 2013. [<http://dx.doi.org/10.1016/j.simpat.2013.05.007>]
- [11] L. Jie, Z. Fangfang, H.V. Zuylen, and L. Shoufeng, "Calibration of a micro simulation program for a Chinese city, 14th EWGT & 26th MEC & 1st RH", *Procedia Soc. Behav. Sci.*, vol. 20, pp. 263-272, 2011. [<http://dx.doi.org/10.1016/j.sbspro.2011.08.032>]
- [12] S. Pandian, S. Gokhale, and A.K. Ghoshal, "Evaluating effects of traffic and vehicle characteristics on vehicular emissions near traffic intersections", *Transp. Res. Part D Transp. Environ.*, vol. 14, pp. 180-196, 2009. [<http://dx.doi.org/10.1016/j.trd.2008.12.001>]
- [13] K. Ahn, H. Rakha, A. Trani, and M.V. Aerde, "Estimating vehicle fuel consumption and emissions based on instantaneous speed and acceleration levels", *J. Transp. Eng.*, vol. 128, pp. 182-190, 2002. [[http://dx.doi.org/10.1061/\(ASCE\)0733-947X\(2002\)128:2\(182\)](http://dx.doi.org/10.1061/(ASCE)0733-947X(2002)128:2(182))]
- [14] A. Papson, S. Hartley, and K. Kuo, "Analysis of emissions at congested and uncongested intersections with motor vehicle emission simulation 2010", *Transp. Res. Rec.*, no. 2270, pp. 124-131, 2012. [<http://dx.doi.org/10.3141/2270-15>]
- [15] D.J. Sun, Y. Zhang, R. Xue, and Y. Zhang, "Modeling carbon emissions from urban traffic system using mobile monitoring", *Sci. Total Environ.*, vol. 599-600, pp. 944-951, 2017. [<http://dx.doi.org/10.1016/j.scitotenv.2017.04.186>] [PMID: 28505886]
- [16] D.J. Sun, K. Zhang, and S. Shen, "Analyzing spatiotemporal traffic line source emissions based on massive online car-hailing service data", *Transp. Res. Part B*, vol. 62, pp. 699-714, 2018. [<http://dx.doi.org/10.1016/j.trd.2018.04.024>]

- [17] A. Csikos, and I. Varga, "Real-time modeling and control objective analysis of motorway emissions", *Procedia Soc. Behav. Sci.*, vol. 54, pp. 1027-1036, 2012.  
[<http://dx.doi.org/10.1016/j.sbspro.2012.09.818>]
- [18] H. Abou-Senna, E. Radwan, K. Westerlund, and C.D. Cooper, "Using a traffic simulation model (VISSIM) with an emissions model (MOVES) to predict emissions from vehicles on a limited-access highway", *J. Air Waste Manage. Assoc.*, 63(7), pp. 2162-2906 *Online (Bergh)*, 2013. [Accessed Des. 21, 2017].  
[<http://dx.doi.org/10.1080/10962247.2013.795918>]
- [19] X. Xu, H. Liu, Y. Xu, M.P. Hunter, M.O. Rodgers, and R.L. Guensler, "Estimating project-level vehicle emissions with vissim and moves-matrix", *Transp. Res. Rec.*, no. 2570, pp. 107-117, 2016.  
[<http://dx.doi.org/10.3141/2570-12>]

© 2018 Arliansyah and Bawono.

This is an open access article distributed under the terms of the Creative Commons Attribution 4.0 International Public License (CC-BY 4.0), a copy of which is available at: <https://creativecommons.org/licenses/by/4.0/legalcode>. This license permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.



# Analysis of the Emission Reduction through Performance Improvement of Intersection and Network nearby Using Micro Simulation Program

ORIGINALITY REPORT

8%

SIMILARITY INDEX

PRIMARY SOURCES

- |   |  |               |
|---|--|---------------|
| 1 | Hatem Abou-Senna, Essam Radwan, Kurt Westerlund, C. David Cooper. "Using a traffic simulation model (VISSIM) with an emissions model (MOVES) to predict emissions from vehicles on a limited-access highway", <i>Journal of the Air &amp; Waste Management Association</i> , 2013<br><small>Crossref</small> | 64 words — 1% |
| 2 | <a href="http://art.torvergata.it">art.torvergata.it</a><br><small>Internet</small>  | 53 words — 1% |
| 3 | <a href="http://benthamopen.com">benthamopen.com</a><br><small>Internet</small>  | 50 words — 1% |
| 4 | J Arliansyah, R T Bawono. "Study on Performance of Intersection Around The Underpass Using Micro Simulation Program", <i>IOP Conference Series: Earth and Environmental Science</i> , 2018<br><small>Crossref</small>  | 41 words — 1% |
| 5 | <a href="http://www.tandfonline.com">www.tandfonline.com</a><br><small>Internet</small>  | 36 words — 1% |
| 6 | <a href="http://www.readbag.com">www.readbag.com</a><br><small>Internet</small>  | 35 words — 1% |
| 7 | João Dalto Viganó Pastro, Adriana Cândida Albuquerque Nogueira, Karina Maria Salvatore de Freitas, Fabricio Pinelli Valarelli et al. "Factors Associated to Apical Root Resorption after Orthodontic Treatment", <i>The Open Dentistry Journal</i> , 2018  | 29 words — 1% |

8 Faustin Habyarimana, Temesgen Zewotir, Shaun Ramroop. "Spatial Distribution and Analysis of Risk Factors Associated with Anemia Among Women of Reproductive Age: Case of 2014 Rwanda Demographic and Health Survey Data", The Open Public Health Journal, 2018 26 words — 1%

Crossref

9 "Data Analytics: Paving the Way to Sustainable Urban Mobility", Springer Nature, 2019 21 words — < 1%

Crossref

10 Gowri Sivaramakrishnan, Kannan Sridharan. "Oral Ketorolac with Inferior Alveolar Nerve Block for Irreversible Pulpitis: A Systematic Review and Meta-analysis", The Open Dentistry Journal, 2018 15 words — < 1%

Crossref

11 Mohammed Jasim AL Juboori, Mohammed Ahmed AL Attas, Raquel Zita Gomes, Basma Fathi Alanbari. "Using Resonance Frequency Analysis to Compare Delayed and Immediate Progressive Loading for Implants Placed in the Posterior Maxilla: A Pilot Study", The Open Dentistry Journal, 2018 8 words — < 1%

Crossref

12 Khaled Shaaban, Hatem Abou-Senna, Dina Elnashar, Essam Radwan. "Assessing the impact of converting roundabouts to traffic signals on vehicle emissions along an urban arterial corridor in Qatar", Journal of the Air & Waste Management Association, 2018 7 words — < 1%

Crossref