

Bit--error

by Irmeilyana Irmeilyana

Submission date: 03-May-2023 04:58AM (UTC+0700)

Submission ID: 2082452449

File name: 7.Bit_Error_Rate_BER_QoS_attribute_-2018.pdf (541.09K)

Word count: 4363

Character count: 19715

Bit Error Rate (BER) QoS Attribute in Solving Wireless Pricing Scheme on Single Link Multi Service Network

Irmeilyana, Fitri Maya Puspita, Indrawati, Rahayu Tamy Agustin

Department of Mathematics, Faculty of Mathematics and Natural Sciences, Sriwijaya University, Indonesia

Article Info

Article history:

Received Aug 9, 2017
Revised Sep 14, 2017
Accepted Oct 11, 2017

Keyword:

ABSTRACT

Pricing schemes were set up on multi service network of wireless internet pricing scheme to proposed models applying Bit Error Rate QoS attribute due to requirements for ISP to maximize revenue and provide high quality of service to end users. The model was designed by improving the original model together with added parameters and variables to the model of multi- service network by setting the base price (α) and premium quality (β) as variables and parameters. LINGO 11.0 were applied to help finding the solution. The results show that the improved models yield maximum revenue for ISP by applying the improved model by setting up a variable α and β as constant as well as by increasing the cost of all the changes in QoS. The QoS attribute BER is proven to achieve the ISP's goal to maximize the revenue.

Copyright © 2018 Institute of Advanced Engineering and Science.
All rights reserved.

Corresponding Author:

Fitri Maya Puspita
Department of Mathematics,
Faculty of Mathematics and Natural Sciences,
Sriwijaya University,
Jln. Raya Palembang-Prabumulih, KM 32 Inderalaya Ogan Ilir 30662 South Sumatera, Indonesia.
Email: pipitmac140201@gmail.com

1. INTRODUCTION

The use of the internet by large segments of the community provides an important role in economic life. In this era of internet usage has reached the wireless internet. Economically, the use of wireless internet is cheaper than using a wired internet. This situation provides a great challenge for ISPs in arranging appropriate financing scheme and can provide maximum benefit ISPs and service users [1]. Many applications are developed by utilizing the wireless network, one of these are wireless sensor network applied in many application in wide area or technology [2] such as military or in agriculture [3], [4].

Problem of internet pricing was introduced by [5] and followed by [6-8] in wired network both multi classes and multi service. Then the research continue on focusing the wireless network with the advancement of this era. Problem concerning with the wireless network is not only focus on the pricing schemes but many aspect can be reviewed and discussed. Scheduling and routing are one of the problems occurring in optimizing the wireless network [9] or using heuristics method described in [10].

Recent research is already discussed by [11] that focused on pricing scheme on wireless of multi class QoS network where by applying some classes in single link network with the various QoS change and connection change. Their result can prove that by increasing connection cost and QoS change along with the cost change, can benefit providers by applying bit error rate (BER) QoS attribute. Based on the critical views of advancement of pricing strategy involving wireless network in multi service network, then it is important to have deeply discussion about that matter.

So, in this paper, the financing schemes bottled single link formed by with bit error rate QoS attribute and the network model multi service proposed by [12], [13] to fix the basic price (α) and premium (β) will be resolved by considering the financing model wireless networks optimally solved using LINGO

program 11.0. the solution then will be compared to other QoS attribute to seek the best QoS attribute to be applied by ISP. The solutions can be expected to be used in order to maximize revenues ISP and provide the best quality services for users.

2. RESEARCH METHOD

In this study, the financing scheme single link wireless internet by multi service network is completed with 11.0 LINGO program that can solve the nonlinear model to get the optimal solution. The model used is modified model by combining the original model proposed by [14] with BER QoS attributes and in multi-service network model. The data used to test the model of secondary data obtained from one of the local server in Palembang, where data used consisted of mail, file and IP camera traffic data.

3. RESULTS AND ANALYSIS

This section explains about the model develop by applying BER QoS attribute, along with the parameters and variables defined.

3.1. Modified Models

In the modified model, the model developed by combining with the network model in multi service network by adding parameters, variable decisions and constraints of each model and setting base price (α) and premium quality (β). wireless internet financing schemes on the modified model for QoS attribute BER is divided into four (4) cases based on the value of the model modification, PQ_{ij} dan x .

Parameters used in the modified models are as follows.

R	: Function of revenue
PR_{ik}	: Cost to connect with available QoS
PQ_{ik}	: Cost changes along with QoS change
x	: An increase or decrease on QoS value
Q_{bik}	: Nominal value of QoS attributes in operator network
PB_{ik}	: Base value for a connection in service i and link k
Lx	: Linearity factor
a_{ik}	: Linear cost factor in service i and link k
T_l	: Traffic load
a	: Predetermined linear parameter
B	: Predetermined linear parameter
f	: Minimum value set by service provider for a_{ik}
g	: Maximum value set by service provider for a_{ik}
h	: Number of minimum traffic load allowable for T_l
k	: Number of maximum traffic load allowable for T_l
I_i	: Quality index for service i
p_{ik}	: Price for user of service i in link k
x_{ik}	: Number of users in service i in link k
d_{ik}	: Capacity needed for service i in link k
C_k	: Total capacity in link k
a_{ik}	: Total capacity of i in link k
m_i	: QoS minimum for service i
n_i	: Number of users in service i
l_i	: Minimum quality premium for service i
b_i	: Maximum kualitas premium untuk layanan i
y	: Minimum base price for service i
z	: Maximum base price for service i

There are four cases which are the case of α and β as parameters, as the case α and β parameter and variables, case α and β as variables and case variables α and β as parameter.

3.1.1. Modified Model for α and β Parameter of BER QoS Attribute

Wireless pricing scheme model of modified case of α and β sebagai parameter, then the objective function will be as :

$$\text{Max } R = \sum_{k=1}^r \sum_{i=1}^s PR_{ik} \pm PQ_{ik} + ((\alpha + \beta \cdot I_i) \cdot p_{ik} \cdot x_{ik}) \quad (1)$$

Bit Error Rate (BER) QoS Attribute in Solving Wireless Pricing Scheme on Single Link ... (Irmeilyana)

Subject to

$$PQ_{11} = \left(1 \pm \frac{x}{10^{-7}}\right) PB_{11} Lx \quad (2)$$

$$PQ_{21} = \left(1 \pm \frac{x}{10^{-7}}\right) PB_{21} Lx \quad (3)$$

$$PQ_{31} = \left(1 \pm \frac{x}{10^{-7}}\right) PB_{31} Lx \quad (4)$$

$$PB_{11} = a_{11}(e - e^{-xB})T_l/100 \quad (5)$$

$$PB_{21} = a_{21}(e - e^{-xB})T_l/100 \quad (6)$$

$$PB_{31} = a_{31}(e - e^{-xB})T_l/100 \quad (7)$$

$$Lx = (e - e^{-xB}) \quad (8)$$

$$0.05 \leq a_{11} \leq 0.15 \quad (9)$$

$$0.06 \leq a_{21} \leq 0.14 \quad (10)$$

$$0.07 \leq a_{31} \leq 0.13 \quad (11)$$

$$50 \leq T_l \leq 1000 \quad (12)$$

$$0 \leq x \leq 1 \quad (13)$$

$$0.8 \leq B \leq 1.07 \quad (14)$$

$$a = 1 \quad (15)$$

$$I_1 x_{11} \leq a_{11} \quad (16)$$

$$I_2 x_{21} \leq a_{21} \quad (17)$$

$$I_3 x_{31} \leq a_{31} \quad (18)$$

$$I_1 x_{11} + I_2 x_{21} + I_3 x_{31} \leq C \quad (19)$$

$$a_{11} + a_{21} + a_{31} = 1 \quad (20)$$

$$0 \leq a_{11} \leq 1 \quad (21)$$

$$0 \leq a_{21} \leq 1 \quad (22)$$

$$0 \leq a_{31} \leq 1 \quad (23)$$

$$0.01 \leq I_1 \leq 1 \quad (24)$$

$$0.01 \leq I_2 \leq 1 \quad (25)$$

$$0.01 \leq I_3 \leq 1 \quad (26)$$

$$0 \leq x_{11} \leq 1 \quad (27)$$

$$0 \leq x_{21} \leq 10 \quad (28)$$

$$0 \leq x_{31} \leq 10 \tag{29}$$

$$\{x_{11}, x_{21}, x_{31}\} \subseteq \mathbb{Z}^+ \tag{30}$$

By modifying the index quality $i (I_i)$ which is

$$\text{if } I_i = I_{i-1}, \text{ then add the constraint} \tag{31}$$

$$I_3 - I_2 = 0 \tag{32}$$

Based on Objectivefunction (1) and Equation (2) to Equation (32), the optimal solution for each case based on BER QoS attribute will be solved by using LINGO 11.0.

Table 1. Optimal Solution of Modified Model of Wireless Internet Pricing Scheme on BER QoS Attribute for α and β Parameter

Variables	PQ _{ik} increase x increase	PQ _{ik} increase x decrease	PQ _{ik} decrease x increase	PQ _{ik} decrease x decrease
Model Class	INLP	INLP	INLP	INLP
State	Local Optimal	Local Optimal	Local Optimal	Local Optimal
Objective	5.64192 x 10 ⁸	98.7587	67.7576	69.2338
Infeasibility	0	0	0	5.82 x 10 ¹¹
Iterations	14	21	12	13
GMU	32K	32K	32K	32K
ER	0s	0s	0s	0s

Based on Table 1, the value will achieve the most optimal results in the first case which is equal to 5.64192 x 108. These results will be obtained by iterating 14 iterations of the infeasibility of 0. Generated Memory Used (GMU) t is 32K and Elapsed Runtime (ER) is 0 seconds.

Based on Table 2 it can be seen that the values of variables PQ_{ij} for case 1 is very big, for case 2 and 3 is quite big, while in four case 4 the values of variables is 0. In case 1 the value of x is 1, whereas in cases 2 and 3 the value of x adala h 0, in case 4the value of x is 10-7 or close to 0. Value of PB_{ij} for case 1 and 2 is different but not much different whereas the value of PB_{ij} for cases 3 and 4 approaches 0 and quite different from the value of PB_{ij} in case 1 and 2. Values of L_x in case 1 is 2.375273 while in cases 1, 2 and 3, the cases have variable the same values of L_x. Value of aik in case 1 and 3 is the same one, not much different from the case 2 and case 4 in which case 2 and 4 have the values of the same variable.

Table 2. Value of Decision Variables in Modified Model for BER QoS Attribute for α and β Parameter

Variables	PQ _{ik} increase x increase	PQ _{ik} increase x decrease	PQ _{ik} decrease x increase	PQ _{ik} decrease x decrease
PQ ₁₁	2.905738	2.902833	0.075407	0.075407
PQ ₂₁	0.600000	7.894743	0.206674	0.206674
PQ ₃₁	45.63906	49.59345	1.194164	1.194164
x	1	1	0	0
PB ₁₁	1.222716	1.222716	0.043885	0.043885
PB ₂₁	3.325383	3.325383	0.120279	0.120279
PB ₃₁	19.20463	19.20463	0.694975	0.694975
PR ₁₁	0.5	0.5	0.5	0.5
PR ₂₁	0.6	0.6	0.6	0.6
PR ₃₁	0.7	0.7	0.7	0.7
a ₁₁	0.05	0.05	0.05	0.05
a ₂₁	0.14	0.14	0.14	0.14
a ₃₁	0.81	0.81	0.81	0.81
L _x	2.375273	2.375273	1.718282	1.718282
T ₁	1000	1000	1000	1000
a	1	1	1	1
B	1.07	1.07	1.07	1.07
I ₁	0.014	0.014	0.014	0.014
I ₂	0.014	0.014	0.014	0.014
I ₃	0.014	0.014	0.014	0.014
x ₁₁	10	10	10	10
x ₂₁	10	10	10	10
x ₃₁	10	10	10	10

3.1.2. Modified Model of α Parameter and β Variable of BER QoS Attribute

The model of wireless pricing for the case of α parameter and β variable is as follows:

$$Max R = \sum_{k=1}^r \sum_{i=1}^s PR_{ik} \pm PQ_{ik} + ((\alpha + \beta_i \cdot I_i) \cdot p_{ik} \cdot x_{ik}) \tag{33}$$

Subject to Equation (2) to Equation (32) with added constraints as follows:

$$\beta_2 I_2 \geq \beta_1 I_1 \tag{34}$$

$$\beta_3 I_3 \geq \beta_2 I_2 \tag{35}$$

$$0,01 \leq \beta_1 \leq 0,5 \tag{36}$$

$$0,01 \leq \beta_2 \leq 0,5 \tag{37}$$

$$0,01 \leq \beta_3 \leq 0,5 \tag{38}$$

When we modify the quality index i (I_i) and quality premium (β_i) then

if $\beta_i = \beta_{i-1}$, add the constraints

$$\beta_2 - \beta_1 = 0 \tag{39}$$

$$\beta_3 - \beta_2 = 0 \tag{40}$$

According to objective (33) and Equation (2) to Equation (32) also Equation (34) to Equation (40) the optimal solution can be completed by applying LINGO 11.0.

Based on Table 3, the value achieves the most optimal results in the first case which is equal to 5.64192 x 108. These results will be obtained by iterating 13 times with the infeasibility of 0. The GMU is equal to 34k and ER is 0 seconds.

Table 3. Optimal Solution of Modified Model of Wireless Internet Pricing Scheme on BER QoS Attribute for α Parameter and β Variable

Variables	PQ _{ik} increase x increase	PQ _{ik} increase x decrease	PQ _{ik} decrease x increase	PQ _{ik} decrease x decrease
Model Class	INLP	INLP	INLP	INLP
State	Local Optimal	Local Optimal	Local Optimal	Local Optimal
Objective	5.64192 x 10 ⁸	98.7487	67.7576	58.5797
Infeasibility	0	0	0	0
Iterations	13	15	11	13
GMU	34K	34K	34K	34K
ER	0s	0s	0s	0s

According to Table 4, it can be examined that the value of PQ_{ij} for case 1 is very big, while in case 2 and 3 are quite big and case 4 is 0. x value of case 1 is 1, as for case 2 and 3 are 0, then for case 4 is 10^{-7} or close to 0. PB_{ij} value for case 1 and 2 is not much different, but it occurs differently from case 1 and 2 for case 3 and 4 which are tend to 0 Value of L_x in case 1 is 2.375273 where I case 1, 2 and 3, the value of L_x is the same. Value of a_{ik} in case 1 and 3 is same, but not quite much different with the value of case 2 and 4 which have the same variable value.

Table 4 Value of Decision Variables in Modified Model for BER QoS Attribute for α Parameter and β Variable

Variables	PQ _{ik} increase x increase	PQ _{ik} increase x decrease	PQ _{ik} decrease x increase	PQ _{ik} decrease x decrease
PQ ₁₁	2.82 x 10 ⁷	4.428739	0.073812	0
PQ ₂₁	7.89 x 10 ⁷	4.133489	0.206674	0
PQ ₃₁	45.69 x 10 ⁷	20.96270	1.195759	0
x	1	0	0	1 x 10 ⁻⁷
PB ₁₁	1.187637	2.577423	0.042957	0.128871
PB ₂₁	3.325383	2.405595	0.120279	0.120279
PB ₃₁	19.23971	12.19980	0.695904	0.609990
PR ₁₁	0.5	0.5	0.5	0.5
PR ₂₁	0.6	0.6	0.6	0.6
PR ₃₁	0.7	0.7	0.7	0.7
a ₁₁	0.05	0.15	0.05	0.15
a ₂₁	0.14	0.14	0.14	0.14
a ₃₁	0.81	0.71	0.81	0.71
L _k	2.375273	1.718282	1.718282	1.718282
T ₁	1000	1000	1000	1000
a	1	1	1	1
B	1.07	1.07	1.07	1.07
I ₁	0014	0.014	0.014	0.014
I ₂	0.014	0.014	0.014	0.014
I ₃	0.014	0.014	0.014	0.014
x ₁₁	10	10	10	10
x ₂₁	10	10	10	10
x ₃₁	10	10	10	10
β ₁	0.5	0.5	0.5	0.5
β ₂	0.5	0.5	0.5	0.5
β ₃	0.5	0.5	0.5	0.5

3.1.3. Modified Model for α dan β Variable of BER QoS attribute

The objective function will be

$$Max R = \sum_{k=1}^r \sum_{i=1}^s PR_{ik} \pm PQ_{ik} + ((\alpha_i + \beta_i \cdot I_i) \cdot p_{ik} \cdot x_{ik}) \tag{41}$$

Subject to Equation (2) to Equation (32) and Equation (36) to Equation (38) with added constraints as follows:

$$\alpha_2 + \beta_2 I_2 \geq \alpha_1 + \beta_1 I_1 \tag{42}$$

$$\alpha_3 + \beta_3 I_3 \geq \alpha_2 + \beta_2 I_2 \tag{43}$$

$$0 \leq \alpha_1 \leq 1 \tag{44}$$

$$0 \leq \alpha_2 \leq 1 \tag{45}$$

$$0 \leq \alpha_3 \leq 1 \tag{46}$$

and, if $\alpha_i = \alpha_{i-1}$, then

$$\alpha_2 - \alpha_1 = 0 \tag{47}$$

$$\alpha_3 - \alpha_2 = 0 \tag{48}$$

Next, for objective function (41) subject to Equation (2) to Equation (32), Equation (36) to Equation (38) and Equation (42) to Equation (48), the optimal solution for each case is completed with LINGO 11.0.

Based on Table 5 the value will achieve the most optimal results in the first case is equal to 5.64192 x 108. These results will be obtained by iterating by 14 iterations of the infeasibility of 0. The GMU is equal to 35K and ER is 0 seconds. According to Table 6 we can examine that the variable values of PQ_{ij} for case 1 is very big, for case 2 and 3 variable values PQ_{ij} are quite big, for case 4, the variable values for case 4

PQ_{ij} is 0. In case 1, the value x is 1, while for case 2 and 3 the value of x is 0, and for case 4 the value of x is 10^{-7} or close 0. The other values of decision variable can be seen completely in Table 5.

Table 5 Optimal Solution of Modified Model of Wireless Internet Pricing Scheme on BER QoS Attribute for α and β Variable

Variables	PQ_{ik} increase x increase	PQ_{ik} increase x decrease	PQ_{ik} decrease x increase	PQ_{ik} decrease x decrease
Model Class	INLP	INLP	INLP	INLP
State	Local Optimal	Local Optimal	Local Optimal	Local Optimal
Objective	5.64192×10^8	665,759	634,758	636,234
Infeasibility	0	0	4.43×10^{-2}	0
Iterations	14	14	32	23
GMU	35K	35K	35K	35K
ER	0s	0s	0s	0s

Table 6. Value of Decision Variables in Modified Model for BER QoS Attribute for α and β Variable

Variables	PQ_{ik} increase x increase	PQ_{ik} increase x decrease	PQ_{ik} decrease x increase	PQ_{ik} decrease x decrease
PQ_{11}	2.82×10^7	4.428739	0.073812	0
PQ_{21}	7.89×10^7	4.133489	0.206674	0
PQ_{31}	45.69×10^7	20.96270	1.195759	0
x	1	0	0	1×10^{-7}
PB_{11}	1.187637	2.577423	0.042957	0.128871
PB_{21}	3.325383	2.405595	0.120279	0.120279
PB_{31}	19.23971	12.19980	0.695904	0.609990
PR_{11}	0.5	0.5	0.5	0.5
PR_{21}	0.6	0.6	0.6	0.6
PR_{31}	0.7	0.7	0.7	0.7
a_{11}	0.05	0.15	0.05	0.15
a_{21}	0.14	0.14	0.14	0.14
a_{31}	0.81	0.71	0.81	0.71
L_x	2.375273	1.718282	1.718282	1.718282
T_1	1000	1000	1000	1000
a	1	1	1	1
B	1.07	1.07	1.07	1.07
I_1	0.014	0.014	0.014	0.014
I_2	0.014	0.014	0.014	0.014
I_3	0.014	0.014	0.014	0.014
x_{11}	10	10	10	10
x_{21}	10	10	10	10
x_{31}	10	10	10	10
α_1	1	1	1	1
α_2	1	1	1	1
α_3	1	1	1	1
β_1	0.5	0.5	0.5	0.5
β_2	0.5	0.5	0.5	0.5
β_3	0.5	0.5	0.5	0.5

3.1.4. Modified Model Modifikasi for α Variable and dan β Parameter of BER QoS Attribute

The objective function will be as follows.

$$Max R = \sum_{k=1}^r \sum_{i=1}^s PR_{ik} \pm PQ_{ik} + ((\alpha_i + \beta \cdot I_i) \cdot p_{ik} \cdot x_{ik}) \tag{49}$$

Subject to Equation (2) to Equation (32), Equation (47) to Equation (48) and Equation (44) to Equation (46) also, with added constraints as follows:

$$\alpha_2 + I_2 \geq \alpha_1 + I_1 \tag{50}$$

$$\alpha_3 + I_3 \geq \alpha_2 + I_2 \tag{51}$$

Then the solution is presented in Table 7 and Table 8. In Table 7, the optimal solution is achieved in case 1 of 5.64192×10^8 while in Table 8 the solver status explains the detail of the solution done by LINGO 11.0.

Table 7. Optimal Solution of Modified Model of Wireless Internet Pricing Scheme on BER QoS Attribute for α Variable and β Parameter

Variables	PQ _{ik} increase x increase	PQ _{ik} increase x decrease	PQ _{ik} decrease x increase	PQ _{ik} decrease x decrease
Model Class	INLP	INLP	INLP	INLP
State	Local Optimal	Local Optimal	Local Optimal	Local Optimal
Objective	5.64192 x 10 ⁸	665.759	634.758	636.234
Infeasibility	0	8.88 x 10 ⁻¹⁶	2.28 x 10 ⁻²	0
Iterations	15	20	29	21
GMU	35K	35K	35K	35K
ER	0s	0s	0s	0s

Table 8. Value of Decision Variables in Modified Model for BER QoS Attribute for α Variable and β Parameter

Variables	PQ _{ik} increase x increase	PQ _{ik} increase x decrease	PQ _{ik} decrease x increase	PQ _{ik} decrease x decrease
PQ ₁₁	2.82 x 10 ⁷	2.739399	0.073812	0
PQ ₂₁	7.89 x 10 ⁷	4.133489	0.206674	0
PQ ₃₁	45.69 x 10 ⁷	22.65204	1.195759	0
x	1	0	0	1 x 10 ⁷
PB ₁₁	1.187637	1.594266	0.042957	0.128871
PB ₂₁	3.325383	2.405595	0.120279	0.120279
PB ₃₁	19.23971	13.18296	0.695904	0.609990
PR ₁₁	0.5	0.5	0.5	0.5
PR ₂₁	0.6	0.6	0.6	0.6
PR ₃₁	0.7	0.7	0.7	0.7
a ₁₁	0.05	0.10	0.10	0.10
a ₂₁	0.14	0.14	0.14	0.14
a ₃₁	0.81	0.76	0.81	0.1
L _x	2.375273	1.718282	1.718282	1.718282
T ₁	1000	1000	1000	1000
a	1	1	1	1
B	1.07	1.07	1.07	1.07
I ₁	0.014	0.014	0.014	0.014
I ₂	0.014	0.014	0.014	0.014
I ₃	0.014	0.014	0.014	0.014
x ₁₁	10	10	10	10
x ₂₁	10	10	10	10
x ₃₁	10	10	10	10
α ₁	1	1	1	1
α ₂	1	1	1	1
α ₃	1	1	1	1

Table 9, Table 10 and Table 11 displays the comparison between other QoS attribute such as bandwidth, End to End delay and BER. According to Table 10, the optimal solution was achieved for case 3 and 4.

Table 9 The Comparison of Modified Model for Bandwidth QoS Attribute

Variables	Modified Model			
	α and β Parameter	α Parameter and β variable	α and β variable	α variable and β Parameter
Model Class	INLP	INLP	INLP	INLP
State	Local Optimal	Local Optimal	Local Optimal	Local Optimal
Objective	125.681	125.681	634.758	692.681
Infeasibility	0	1.5 x 10 ⁻²	1.11 x 10 ⁻¹⁶	0
Iterations	13	24	23	13
GMU	32K	32K	35K	35K
ER	0s	0s	0s	0s

It can be seen in Table 11, the same value occurs for each case of BER QoS attribute which is 5,64192 x 10⁸. It can be concluded for each QoS attribute, the optimal solution occurs in case 1 where increasing cost along with QoS change (PQ_{ik}) and increase the value of (x) where the revenue of IDR 564,192,000 is obtained.

Table 10. The Comparison of Modified Model for End To End QoS Attribute

Variables	Modified Model			
	α and β Parameter	α Parameter and β variable	α and β variable	α variable and β Parameter
Model Class	INLP	INLP	INLP	INLP
State	Local Optimal	Local Optimal	Local Optimal	Local Optimal
Objective	125.814	125.814	692.814	692.814
Infeasibility	0	0	0	0
Iterations	13	12	12	12
GMU	32K	34K	35K	35K
ER	0s	0s	0s	0s

Table 11. The Comparison of Modified Model for BER Attribute

Variables	Model Modifikasi			
	α and β Parameter	α Parameter and β variable	α and β variable	α variable and β Parameter
Model Class	INLP	INLP	INLP	INLP
State	Local Optimal	Local Optimal	Local Optimal	Local Optimal
Objective	5.64192×10^8	5.64192×10^8	5.64192×10^8	5.64192×10^8
Infeasibility	0	0	0	0
Iterations	14	13	14	15
GMU	32K	34K	35K	35K
ER	0s	0s	0s	0s

4. CONCLUSION

According to results above, the model for each attribute, we can conclude that ISP obtains maximum revenue by fixing the pricing strategy in multi service according to BER QoS attribute by increasing the cost along QoS change (PQ_{ik}) and the value of QoS (x) with the profit of IDR 564,192,000.

ACKNOWLEDGEMENTS

The research leading to this study was financially supported by Directorate of Higher Education Indonesia (DIKTI) for support through "Hibah Bersaing Tahun II", 2016.

REFERENCES

- [1] E.R.Wallenius, "Control and Management of Multi-Access Wireless Network," in *Mathematical Information Technology*. 2005, University of Jyväskylä: Jyväskylä.
- [2] J. Rezaadeh, et al., "Fundamental Metrics for Wireless Sensor Networks localization," *International Journal of Electrical and Computer Engineering (IJECE)* 2012, 2(4): p. 452-455.
- [3] S. Su and S. Wang, "A simple monitoring network system of Wireless Sensor Network", *Buletin Teknik Elektro dan Informatika (Bulletin of Electrical Engineering and Informatics)* 2012, 1(4): p. 251-254.
- [4] X. Yan, et al., "A Wireless Sensor Network in Precision Agriculture," *TELKOMNIKA (Telecommunication Computing Electronics and Control)*, 2012, 10(4): p. 788-797.
- [5] W. Yang, et al., "Determining Differentiated Services Network Pricing Through Auctions," in *Networking-ICN 2005*, 4th International Conference on Networking April 2005 Proceedings, Part I. 2005. Reunion Island, France: Springer-Verlag Berlin Heidelberg.
- [6] F.M. Puspita, et al., "Improved Models of Internet Charging Scheme of Single Bottleneck Link in Multi QoS Networks," *Journal of Applied Sciences*, 2013. 13(4): p. 572-579.
- [7] F.M. Puspita, et al., "The Improved Models of Internet Pricing Scheme of Multi Service Multi Link Networks with Various Capacity Links," in *Advanced Computer and Communication Engineering Technology*.
- [8] H.A. Sulaiman, et al., Editors. 2015, Springer International Publishing: Switzerland.
- [9] E. Safari, et al., "Determining strategy of pricing for a web service with different QoS levels and reservation level constraint," *Applied Mathematical Modelling*, 2014.
- [10] N.M. Adriansyah, et al., "Modified Greedy Physical Link Scheduling Algorithm for Improving Wireless Mesh Network Performance," *TELKOMNIKA (Telecommunication Computing Electronics and Control)*, 2015. 13(1): p. 202-210.
- [11] J. Li, and X. Tian, "Application of Ant Colony Algorithm in Multi-objective Optimization Problems," *TELKOMNIKA (Telecommunication Computing Electronics and Control)*, 2015. 13(3): p. 1029-1036.
- [12] Irmeilyana, et al., "Optimization of Wireless Internet Pricing Scheme in Serving Multi QoS Network Using Various QoS Attributes," *TELKOMNIKA (Telecommunication, Computing, Electronics and Control)*, 2016. 14(1).

- [13] S. Sain and S. Herpers, "Profit Maximisation in Multi Service Networks- An Optimisation Model," in Proceedings of the 11th European Conference on Information Systems ECIS 2003. 2003. Naples, Italy
- [14] J. Byun and S. Chatterjee, "A strategic pricing for quality of service (QoS) network business," in Proceedings of the Tenth Americas Conference on Information Systems. 2004. New York.
- [15] E. Wallenius and T. Hämäläinen, "Pricing Model for 3G/4G Networks", in The 13th IEEE International Symposium on Personal, Indoor, and Mobile Radio Communications. 2002: Lisbon, Portugal.

BIOGRAPHIES OF AUTHORS



Irmeilyana received her S.Si (Undergraduate Degree in Science) in Mathematics from Bogor Agriculture Institute (IPB) Indonesia in 1997. Then she received her Master Degree in Mathematics from Bandung Technology Institute (ITB) Indonesia in 1999. She has been a Mathematics Department member at Faculty Mathematics and Natural Sciences Sriwijaya University South Sumatera Indonesia since 1999. Her research interests include Statistics, optimization and its applications.



Fitri Maya Puspita received her S.Si degree in Mathematics from Sriwijaya University, South Sumatera, Indonesia in 1997. Then she received her M.Sc in Mathematics from Curtin University of Technology (CUT) Western Australia in 2004. She graduated from Faculty of Science and Technology Islamic Science University of Malaysia (USIM), Nilai, Negeri Sembilan Darul Khusus, Malaysia in 2015. She has been a Mathematics Department member at Faculty mathematics and Natural Sciences Sriwijaya University South Sumatera Indonesia since 1998. Her research interests include optimization and its applications such as vehicle routing problems and QoS pricing and charging in third generation internet.



Indrawati received her received her S.Si degree in Mathematics from Sriwijaya University, South Sumatera, Indonesia in 1996. Then she received M.Si in Mathematics Actuarial from Bandung Institute of Technology, Indonesia in 2004. She has been a Mathematics Department member at Faculty mathematics and Natural Sciences Sriwijaya University South Sumatera Indonesia since 1998. Her research interest includes actuarial science and its applications in insurance and risk theory.



Rahayu Tamy Agustin received her S.Si degree (Bachelor Degree in Science) in Mathematics from Sriwijaya University, South Sumatera, Indonesia in 2016. Her research interest includes Optimization, and its application on internet charging scheme in wireless network.

Bit--error

ORIGINALITY REPORT

15%

SIMILARITY INDEX

13%

INTERNET SOURCES

11%

PUBLICATIONS

4%

STUDENT PAPERS

MATCH ALL SOURCES (ONLY SELECTED SOURCE PRINTED)

3%

★ **iieng.org**

Internet Source

Exclude quotes On

Exclude matches Off

Exclude bibliography On